OIL ANALYSIS REPORT

Area
[GTT224-333]
Machine Id
YORK SMYM479420
Component
Chiller
Fluid
YORK TYPE K (--- GAL)

Sample Rating Trend



DEGRADATION

DIAGNOSIS

Recommendation
We recommend an early resample to monitor this condition.

Wear
All component wear rates are normal.

Contamination
The water content is negligible. There is no indication of any contamination in the oil.

Fluid Condition
The AN level is above the recommended limit. The oil is no longer serviceable.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number		Client Info		**GTT0001618**	GTT69062	GTT69063
Sample Date		Client Info		**12 Mar 2024**	31 May 2022	27 Jul 2021
Machine Age	hrs	Client Info		**0**	---	---
Oil Age	hrs	Client Info		**0**	---	---
Oil Changed		Client Info		**N/A**	N/A	N/A
Sample Status				**ATTENTION**	NORMAL	NORMAL

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>8	**0**	<1	<1
Chromium	ppm	ASTM D5185(m)	>2	**0**	<1	<1
Nickel	ppm	ASTM D5185(m)		**0**	---	---
Titanium	ppm	ASTM D5185(m)		**0**	---	---
Silver	ppm	ASTM D5185(m)	>2	**0**	---	---
Aluminum	ppm	ASTM D5185(m)	>3	**0**	<1	<1
Lead	ppm	ASTM D5185(m)	>2	**0**	<1	<1
Copper	ppm	ASTM D5185(m)	>8	**0**	<1	<1
Tin	ppm	ASTM D5185(m)	>4	**0**	<1	<1
Antimony	ppm	ASTM D5185(m)		**0**	---	---
Vanadium	ppm	ASTM D5185(m)		**0**	---	---
Beryllium	ppm	ASTM D5185(m)		**0**	---	---
Cadmium	ppm	ASTM D5185(m)		**0**	---	---

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	0	**0**	---	---
Barium	ppm	ASTM D5185(m)	0	**0**	---	---
Molybdenum	ppm	ASTM D5185(m)	0	**0**	---	---
Manganese	ppm	ASTM D5185(m)	0	**0**	---	---
Magnesium	ppm	ASTM D5185(m)	0	**0**	---	---
Calcium	ppm	ASTM D5185(m)	0	**0**	---	---
Phosphorus	ppm	ASTM D5185(m)	5	**0**	---	---
Zinc	ppm	ASTM D5185(m)	0	**<1**	<1	<1
Sulfur	ppm	ASTM D5185(m)	10	**13**	---	---
Lithium	ppm	ASTM D5185(m)		**<1**	---	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	**<1**	---	---
Sodium	ppm	ASTM D5185(m)		**<1**	---	---
Potassium	ppm	ASTM D5185(m)	>20	**<1**	---	---
ppm Water	ppm	ASTM D6304*	>300	**128**	77	164

FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.03	**0.18**	0.057	0.093

OIL ANALYSIS REPORT

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	**NONE**	---	---
Yellow Metal	scalar	Visual*	NONE	**NONE**	---	---
Precipitate	scalar	Visual*	NONE	**NONE**	---	---
Silt	scalar	Visual*	NONE	**NONE**	---	---
Debris	scalar	Visual*	NONE	**NONE**	---	---
Sand/Dirt	scalar	Visual*	NONE	**NONE**	---	---
Appearance	scalar	Visual*	NORML	**NORML**	---	---
Odor	scalar	Visual*	NORML	**NORML**	---	---

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	32.0	**32.7**	---	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color				*no image*	*no image*
Bottom				*no image*	*no image*

GRAPHS

Sample No. : GTT0001618
Lab Number : 02624071
Unique Number : 5749190
Test Package : IND 2 (Additional Tests: KV40)

Received : 22 Mar 2024
Tested : 26 Mar 2024
Diagnosed : 26 Mar 2024 - Bill Quesnel

Johnson Controls -Hamilton
40 Hempstead Drive,
Hamilton, ON
CA L8W 2E7
Contact: Service Manager
T:
F:

To discuss this sample report, contact Customer Service at 1-905-847-9300 Ext 26.
Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.