

Chem-Ecol

A2403145

OIL ANALYSIS REPORT

Sample Rating Trend

SAMPLE INFORMATION method limit/base current history1







Component Unknown Component Fluid

CHEM-ECOL HYDRAULIC 46 AWD (--- GAL)

DIAGNOSIS


Recommendation


We certify that this oil is clean, that the additives are at acceptable levels, and that it is suitable for use.


SAMPLE INFORM	/IATION	method	limit/base	current	history 1	history2
Batch #		Client Info		3042-A		
Department		Client Info		Production		
Sample From		Client Info		Machine		
Production Stage		Client Info		Final		
Sent to WC		Client Info		03/21/2024		
Sample Number		Client Info		E30001719		
Sample Date		Client Info		20 Mar 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)		<1		
Chromium	ppm	ASTM D5185(m)		0		
Nickel	ppm	ASTM D5185(m)		0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)		0		
Lead	ppm	ASTM D5185(m)		0		
Copper	ppm	ASTM D5185(m)		1		
Tin	ppm	ASTM D5185(m)		0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<1		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		3		
Calcium	ppm	ASTM D5185(m)		63		
Phosphorus	ppm	ASTM D5185(m)		319		
Zinc	ppm	ASTM D5185(m)		411		
Sulfur	ppm	ASTM D5185(m)		800		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		0		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	0		
· otaootann						
Water	%	ASTM D6304*		0.001		



OIL ANALYSIS REPORT







FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	294		
Particles >6µm		ASTM D7647	>640	100		
Particles >14µm		ASTM D7647	>160	10		
Particles >21µm		ASTM D7647	>40	4		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	15/14/10		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.43		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*		NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	46	44.1		
Visc @ 100°C	cSt	ASTM D7279(m)		7.0		
Viscosity Index (VI)	Scale	ASTM D2270*		116		
SAMPLE IMAGES	6	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image



	CALA	Laboratory	: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9			Environmental 360 Solutions Ltd.
to 1/2 to	Accreditation No. 1006218	Sample No.	: E30001719	Received	: 25 Mar 2024	640 Victoria Street
	Lab Number	: 02624236	Tested	: 26 Mar 2024	Cobourg, ON	
		Unique Number	: 5749355	Diagnosed	: 27 Mar 2024 - Tatiana Sorkina	CA K9A 5H5
	Laboratory	Test Package	: IND 2 (Additiona	I Tests: KF, KV100, I	PrtCount, VI)	Contact: Tatiana Sorkina
	tsorkina@e360s.ca					
	Test denoted (T: (800)263-3939				
	F: (905)373-4950					