

## **OIL ANALYSIS REPORT**

Sample Rating Trend

NORMAL

## **EPIROC MT65 TRK219** Component

Upbox Fluid

## PENNZOIL SYNTHETIC SAE 75W140 GL-5 (--- GAL)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


### Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	<b>IATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0916346		
Sample Date		Client Info		20 Mar 2024		
Machine Age	hrs	Client Info		8262		
Oil Age	hrs	Client Info		500		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>200	7		
Chromium	ppm	ASTM D5185(m)	>10	0		
Nickel	ppm	ASTM D5185(m)	>10	0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)		0		
Lead	ppm	ASTM D5185(m)		0		
Copper	ppm	ASTM D5185(m)		<1		
Tin	ppm	ASTM D5185(m)		0		
Antimony	ppm	ASTM D5185(m)	>5	0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		77		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		<1		
Calcium	ppm	ASTM D5185(m)		17		
Phosphorus	ppm	ASTM D5185(m)		834		
Zinc	ppm	ASTM D5185(m)		8		
Sulfur	ppm	ASTM D5185(m)		17699		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		<1		
Sodium	ppm	ASTM D5185(m)		1		
Potassium	ppm	ASTM D5185(m)	>20	<1		



# **OIL ANALYSIS REPORT**



	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	Visual*	NONE	NONE		
	Yellow Metal	scalar	Visual*	NONE	NONE		
	Precipitate	scalar	Visual*	NONE	NONE		
	Silt	scalar	Visual*	NONE	NONE		
	Debris	scalar	Visual*	NONE	NONE		
	Sand/Dirt	scalar	Visual*	NONE	NONE		
Mar20/24	Appearance	scalar	Visual*	NORML	NORML		
Ma	Odor	scalar	Visual*	NORML	NORML		
	Emulsified Water	scalar	Visual*	>0.2	NEG		
	Free Water	scalar	Visual*		NEG		
	FLUID PROPERT	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D7279(m)	175	182		
	SAMPLE IMAGES	S	method	limit/base	current	history1	history2
	Color					no image	no image
	Bottom					no image	no image
	GRAPHS						
	Iron (ppm)				Lead (ppm)		
	600 Severe				1		
	400 - Abnormal			E O	+		
	0			1			
	Mar20/24			Mar20/24	Mar20/24		Mar20/24
	≥ Aluminum (ppm)			2	≥ Chromium (pp	om)	2
	<sup>1</sup> T			30	Th		
	Ē. 0 -			<sup>20</sup>	Abnormal		
				-10	1		
	0/24						0/24 -
	Mar20,24			Mar20/24	Mar20/24		Mar20/24
	Copper (ppm)			0.3	Silicon (ppm)		
	0.4 0.2			E 0.2			
	<sup>E</sup> 0.2			<sup>-</sup> 0.1			
	Mar20/24 + 0			Mar20/24	Mar20/24		Mar20/24 -
				Mar2			Mar2
	Viscosity @ 40°C			1000	Additives		
	२ 180 - <b>Вазе</b> इर्ज 160 - <b>Abnormal</b>			톱 500	calcium		
					ZINC		
	140 4			0	1/24		124
	Mar20/24			Mar20/24	Mar20/24		Mar20/24
Laboratory Sample No. Lab Number Unique Number Test Package	: WearCheck - C8-1175 : WC0916346 : 02624768 : 5749887 : MOB 1	5 Appleby Recei Teste Diagr	ived : 26 ed : 26	gton, ON L7L 6 Mar 2024 6 Mar 2024 Mar 2024 - Kev	1350 Gove	ernment Rd. W, MA Kirł	Eagle Canada CASSA COMPLEX Cland Lake, ON CA P2N 3J1 ch Lamontagne