

OIL ANALYSIS REPORT

Sample Rating Trend







Machine Id H215 Component Tank Hydraulic System {not provided} (--- GAL)

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Fluid Condition


Viscosity of sample indicates oil is within ISO 32 range, advise investigate. The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0690627		
Sample Date		Client Info		20 Mar 2024		
Machine Age	days	Client Info		7		
Oil Age	days	Client Info		7		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	0		
Chromium	ppm	ASTM D5185(m)	>10	0		
Nickel	ppm	ASTM D5185(m)	>10	0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>10	0		
Lead	ppm	ASTM D5185(m)	>20	0		
Copper	ppm	ASTM D5185(m)	>20	0		
Tin	ppm	ASTM D5185(m)	>10	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		0		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		<1		
Calcium	ppm	ASTM D5185(m)		92		
Phosphorus	ppm	ASTM D5185(m)		187		
Zinc	ppm	ASTM D5185(m)		99		
Sulfur	ppm	ASTM D5185(m)		638		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	0		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	0		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	221		
Particles >6µm		ASTM D7647	>1300	71		
Particles >14µm		ASTM D7647	>160	5		
Particles >21µm		ASTM D7647	>40	1		
Particles >38µm		ASTM D7647	>10	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	15/13/10		
):14:05) Rev: 1		. /			mes Abbew-Jac	



OIL ANALYSIS REPORT

VISUAI








	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	Visual*	NONE	NONE		
	Yellow Metal	scalar	Visual*	NONE	NONE		
	Precipitate	scalar	Visual*	NONE	NONE		
	Silt	scalar	Visual*	NONE	NONE		
	Debris	scalar	Visual*	NONE	NONE		
	Sand/Dirt	scalar	Visual*	NONE	VLITE		
	Appearance	scalar	Visual*	NORML	NORML		
	Odor	scalar	Visual*	NORML	NORML		
	Emulsified Water	scalar	Visual*	>0.05	NEG		
	Free Water	scalar	Visual*		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D7279(m)		31.8		
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
	Color					no image	no image
	Bottom					no image	no image
	GRAPHS						
	Ferrous Alloys				Particle Count	İ.	
	10 8			491,520			T ²⁶
	anneae chromium			122,880	1		-24
				30,720	Severe		-22
	2 -						
				7,680	Abnormal		-20
	Mar20/24			Mar20/24 \$ (per 1 ml)			-18
		1-		Icles (10
	Non-ferrous Meta	IS		pited 480			16
	8 - copper			42/02/2014			-20 -18 -16 -14 +12
	E 6			2 30			+12
	1						
	2				1		-10
	0 74 0			42 2	-		-8
	Mar20/24			Mar20/24			
	∠ Viscosity @ 40°C			- 0	4μ 6μ	14µ 21µ	38µ 71µ
	55 T						
	50 - Abnormal						
	(20 45 정 40 - Abnormal						
				-			
	35						
	30 4			24 +			
	Mar20/24			Mar20/24			
	: WearCheck - C8-117 : WC0690627 : 02624994	5 Appleby Recei Teste	ived : 2		_ 5H9		I Products L 324 Milo Roa HEATLEY, C
r	: 5750113	in Marson	•••	CA NOP 2F			
	: MOB 2	Diagr	-	-		Contact: James A	
			000 000 010				

Test Package : MOB 2 To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

james@hikemetal.com T: (519)825-4691 F: (519)825-7572



CALA

ISO 17025:2017 Accredited Laboratory