




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
Materials Handling/SE Pedestal Crane
 Machine Id
WPD471261 CRANE PEDESTAL SOUTH EAST

Component
Auxiliary Drive
 Fluid
MOBIL MOBILUBE HD 80W90 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.
 NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

Sample Number	Client Info	Method	Limit/Base	Current	History1	History2
Sample Number	Client Info	PP		PP13897520	PP13890909	
Sample Date	Client Info	16 Feb 2024		01 Jul 2023	03 May 2023	
Machine Age	hrs	Client Info	0	0	0	
Oil Age	hrs	Client Info	0	0	0	
Oil Changed	Client Info	N/A		N/A	N/A	
Sample Status		NORMAL		NORMAL	NORMAL	

CONTAMINATION

Water	Method	Limit/Base	Current	History1	History2
Water	WC Method	>0.2	NEG	NEG	NEG

WEAR METALS

PQ	Method	Limit/Base	Current	History1	History2
PQ	ASTM D8184*		0	13	0
Iron	ppm	ASTM D5185(m) >200	3	11	5
Chromium	ppm	ASTM D5185(m) >10	0	0	0
Nickel	ppm	ASTM D5185(m) >10	0	0	0
Titanium	ppm	ASTM D5185(m)	0	0	0
Silver	ppm	ASTM D5185(m)	0	0	0
Aluminum	ppm	ASTM D5185(m)	0	<1	0
Lead	ppm	ASTM D5185(m)	0	<1	0
Copper	ppm	ASTM D5185(m)	0	2	0
Tin	ppm	ASTM D5185(m)	0	0	0
Antimony	ppm	ASTM D5185(m) >5	0	0	0
Vanadium	ppm	ASTM D5185(m)	0	0	0
Beryllium	ppm	ASTM D5185(m)	0	0	0
Cadmium	ppm	ASTM D5185(m)	0	0	0

ADDITIVES

Boron	Method	Limit/Base	Current	History1	History2
Boron	ppm	ASTM D5185(m)	180	174	175
Barium	ppm	ASTM D5185(m)	0	0	0
Molybdenum	ppm	ASTM D5185(m)	0	<1	0
Manganese	ppm	ASTM D5185(m)	0	<1	<1
Magnesium	ppm	ASTM D5185(m)	<1	1	0
Calcium	ppm	ASTM D5185(m)	4	4	2
Phosphorus	ppm	ASTM D5185(m)	1001	1078	1112
Zinc	ppm	ASTM D5185(m)	4	10	7
Sulfur	ppm	ASTM D5185(m)	24438	22283	23368
Lithium	ppm	ASTM D5185(m)	<1	1	<1

CONTAMINANTS




Silicon	Method	Limit/Base	Current	History1	History2
Silicon	ppm	ASTM D5185(m)	0	2	2
Sodium	ppm	ASTM D5185(m)	<1	<1	<1
Potassium	ppm	ASTM D5185(m) >20	<1	<1	<1

FLUID DEGRADATION

Acid Number (AN)	Method	Limit/Base	Current	History1	History2
Acid Number (AN)	mg KOH/g	ASTM D974*	1.47	1.38	1.44




OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	Visual*	NONE	NONE	VLITE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	NONE	VLITE	NONE
Debris	scalar	Visual*	NONE	NONE	VLITE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 40°C	cSt	ASTM D7279(m)	136	140	145	145

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : PP **Received** : 28 Mar 2024
Lab Number : **02625440** **Tested** : 01 Apr 2024
Unique Number : 5750559 **Diagnosed** : 01 Apr 2024 - Wes Davis
Test Package : MAR 2 (Additional Tests: TAN Man)

ExxonMobil Canada East Ltd.
 Hebron-Materials and Repair Coordin, Suite 1000, 100 New Gow
 St. John's, NL
 CA A1C 6K3
 Contact: Liam Maher
 liam.m.maher@exxonmobil.com
 T: (709)273-3729
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.