


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



MANITOU MT625H FOR436

Component

Hydraulic System

{not provided} (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample. Please contact your representative for information regarding the proper sampling kits for your service. NOTE: We recommend using MOB 2 test kits, this testkit includes Particle Count to determine the ISO cleanliness of the fluid.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the component(unconfirmed).

Fluid Condition

The condition of the oil is acceptable for the time in service.

				Mar2024		
SAMPLE INFORM	/ATION	method	limit/base	current	history1	history2
	MATION		IIIIII/Dase		•	· ·
Sample Number		Client Info		WC0916264		
Sample Date	_	Client Info		22 Mar 2024		
Machine Age	hrs	Client Info		839		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	3		
Chromium	ppm	ASTM D5185(m)	>10	0		
Nickel	ppm	ASTM D5185(m)	>10	0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>10	<1		
Lead	ppm	ASTM D5185(m)	>10	0		
Copper	ppm	ASTM D5185(m)	>75	3		
Tin	ppm	ASTM D5185(m)	>10	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<1		
Barium	ppm	ASTM D5185(m)		<1		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		1		
Calcium	ppm	ASTM D5185(m)		29		
Phosphorus	ppm	ASTM D5185(m)		185		
Zinc	ppm	ASTM D5185(m)		221		
Sulfur	ppm	ASTM D5185(m)		5510		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>20	13		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	<1		




OIL ANALYSIS REPORT

cSt

ASTM D7279(m)

Visc @ 40°C



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.1	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	TES	method	limit/base	current	history1	history2

	,				
SAMPLE IMAGES	method			history2	
Color		*******	no image	no image	
Bottom			no image	no image	

33.4

Bottom			no image	no image
GRAPHS				
Iron (ppm) 40 Severe 8 20 Abnormal	30. E 20.	Lead (ppm)		
Mar22/24	Mar22/24	Mar22/24		Mar22/24
Aluminum (ppm) Severe Albormal	30· E 20·	Chromium (pp	om)	
Mar2222-4 ←	Mar22/24	Mar22/24		Mar22/24
Copper (ppm) 300 7 Sewere 100 - Abnormal	60·	Silicon (ppm)		
100 - Abnormal	Mar22/74 0-	Mar 22/24		Mar22/24
Viscosity @ 40°C	300 E 200 E 100	Additives		
30 40 40 40 40 40 40 40 40 40 40 40 40 40	Mar22/24	Mar22/24)	Mar22/24



CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No.

: WC0916264 Lab Number : 02625733 Unique Number : 5750852

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Received **Tested**

Diagnosed : 02 Apr 2024 - Wes Davis

: 01 Apr 2024

: 01 Apr 2024

Agnico Eagle Canada 1350 Government Rd. W, MACASSA COMPLEX

Kirkland Lake, ON CA P2N 3J1 Contact: Mitch Lamontagne

Test Package : MOB 1 To discuss this sample report, contact Customer Service at 1-800-268-2131.

AEM_KL_macassaoilsampleresults@agnicoeagle.com T: (705)567-5208

Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

F: (705)567-5221