



# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**




Area  
**[43978064]**

Machine Id  
**9705**

Component  
**Diesel Engine**

Fluid  
**DIESEL ENGINE OIL SAE 10W30 (--- GAL)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

### Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>WC0924130</b>	WC0796276	---
Sample Date	Client Info			<b>31 Mar 2024</b>	26 Mar 2023	---
Machine Age	kms	Client Info		<b>192511</b>	84763	---
Oil Age	kms	Client Info		<b>0</b>	0	---
Oil Changed	Client Info			<b>Changed</b>	Changed	---
Sample Status				<b>NORMAL</b>	ABNORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>3.0		<b>&lt;1.0</b>	0.8	---
Water	WC Method	>0.2		<b>NEG</b>	NEG	---
Glycol	WC Method			<b>NEG</b>	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>90	<b>19</b>	60	---
Chromium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	2	---
Nickel	ppm	ASTM D5185(m)	>2	<b>&lt;1</b>	1	---
Titanium	ppm	ASTM D5185(m)	>2	<b>0</b>	<1	---
Silver	ppm	ASTM D5185(m)	>2	<b>0</b>	<1	---
Aluminum	ppm	ASTM D5185(m)	>20	<b>12</b>	24	---
Lead	ppm	ASTM D5185(m)	>40	<b>5</b>	8	---
Copper	ppm	ASTM D5185(m)	>330	<b>2</b>	25	---
Tin	ppm	ASTM D5185(m)	>15	<b>&lt;1</b>	5	---
Antimony	ppm	ASTM D5185(m)		<b>0</b>	0	---
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	---
Beryllium	ppm	ASTM D5185(m)		<b>0</b>	0	---
Cadmium	ppm	ASTM D5185(m)		<b>0</b>	0	---


ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	250	<b>30</b>	33	---
Barium	ppm	ASTM D5185(m)	10	<b>0</b>	5	---
Molybdenum	ppm	ASTM D5185(m)	100	<b>2</b>	64	---
Manganese	ppm	ASTM D5185(m)		<b>0</b>	5	---
Magnesium	ppm	ASTM D5185(m)	450	<b>744</b>	440	---
Calcium	ppm	ASTM D5185(m)	3000	<b>1346</b>	1860	---
Phosphorus	ppm	ASTM D5185(m)	1150	<b>681</b>	994	---
Zinc	ppm	ASTM D5185(m)	1350	<b>780</b>	1176	---
Sulfur	ppm	ASTM D5185(m)	4250	<b>2391</b>	2269	---
Lithium	ppm	ASTM D5185(m)		<b>&lt;1</b>	<1	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>25	<b>6</b>	40	---
Sodium	ppm	ASTM D5185(m)		<b>2</b>	5	---
Potassium	ppm	ASTM D5185(m)	>20	<b>30</b>	67	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*	>6	<b>0.2</b>	0.2	---
Nitration	Abs/cm	ASTM D7624*	>20	<b>9.3</b>	9.9	---
Sulfation	Abs.1mm	ASTM D7415*	>30	<b>22.6</b>	25.4	---




# OIL ANALYSIS REPORT



FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs./1mm	ASTM D7414*	>25	<b>17.8</b>	21.5	---
VISUAL		method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	<b>NEG</b>	NEG	---
Free Water	scalar	Visual*		<b>NEG</b>	NEG	---
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	10.9	<b>11.2</b>	▲ 11.5	---

## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : WC0924130      **Received** : 02 Apr 2024  
**Lab Number** : **02626027**      **Tested** : 02 Apr 2024  
**Unique Number** : 5759159      **Diagnosed** : 02 Apr 2024 - Wes Davis  
**Test Package** : MOB 1

**Rush Truck Centres**  
 7450 Torbram Rd.  
 Mississauga, ON  
 CA L4T 1G9  
 Contact: Serdar Okur  
 sokur@rushtruckcentres.ca  
 T: (905)671-7600  
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.