




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Area

## 71 STOCK PREPARATION

Machine Id

### Slusher (Drive) (S/N 715701)

Component

Gear Reducer

Fluid

MOBIL SHC 629 (10 GAL)

#### DIAGNOSIS

##### Recommendation

Resample at the next service interval to monitor.

##### Wear

All component wear rates are normal.

##### Contamination

There is no indication of any contamination in the oil.

##### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

#### SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>WC</b>	WC	WC0789948
Sample Date	Client Info	<b>01 Apr 2024</b>	03 Oct 2023	23 Mar 2023
Machine Age	hrs Client Info	<b>0</b>	0	0
Oil Age	hrs Client Info	<b>0</b>	0	0
Oil Changed	Client Info	<b>N/A</b>	N/A	N/A
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

#### CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG

#### WEAR METALS

method	limit/base	current	history1	history2
PQ	ASTM D8184*	<b>0</b>	0	0
Iron	ppm ASTM D5185(m) >250	<b>15</b>	27	9
Chromium	ppm ASTM D5185(m) >5	<b>0</b>	0	0
Nickel	ppm ASTM D5185(m) >5	<b>0</b>	0	<1
Titanium	ppm ASTM D5185(m)	<b>0</b>	0	0
Silver	ppm ASTM D5185(m)	<b>0</b>	<1	0
Aluminum	ppm ASTM D5185(m) >20	<b>0</b>	<1	<1
Lead	ppm ASTM D5185(m) >50	<b>0</b>	0	0
Copper	ppm ASTM D5185(m) >50	<b>0</b>	<1	0
Tin	ppm ASTM D5185(m) >5	<b>0</b>	0	0
Antimony	ppm ASTM D5185(m) >5	<b>0</b>	<1	<1
Vanadium	ppm ASTM D5185(m)	<b>0</b>	0	0
Beryllium	ppm ASTM D5185(m)	<b>0</b>	0	0
Cadmium	ppm ASTM D5185(m)	<b>0</b>	0	0

#### ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185(m)	<b>&lt;1</b>	<1	1
Barium	ppm ASTM D5185(m)	<b>0</b>	<1	0
Molybdenum	ppm ASTM D5185(m)	<b>0</b>	0	0
Manganese	ppm ASTM D5185(m)	<b>0</b>	0	<1
Magnesium	ppm ASTM D5185(m)	<b>&lt;1</b>	<1	<1
Calcium	ppm ASTM D5185(m)	<b>&lt;1</b>	2	0
Phosphorus	ppm ASTM D5185(m)	<b>459</b>	479	510
Zinc	ppm ASTM D5185(m)	<b>4</b>	8	3
Sulfur	ppm ASTM D5185(m)	<b>127</b>	69	79
Lithium	ppm ASTM D5185(m)	<b>2</b>	9	2

#### CONTAMINANTS




method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185(m) >60	<b>22</b>	35	23
Sodium	ppm ASTM D5185(m)	<b>&lt;1</b>	<1	1
Potassium	ppm ASTM D5185(m) >20	<b>&lt;1</b>	0	1

#### FLUID DEGRADATION

method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g ASTM D974*	<b>0.51</b>	0.59	0.58




# OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	LIGHT	VLITE
Debris	scalar	Visual*	NONE	VLITE	NONE
Sand/Dirt	scalar	Visual*	NONE	VLITE	LIGHT
Appearance	scalar	Visual*	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	142.8	148	148

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : WC **Received** : 05 Apr 2024  
**Lab Number** : 02627116 **Tested** : 08 Apr 2024  
**Unique Number** : 5760248 **Diagnosed** : 08 Apr 2024 - Wes Davis  
**Test Package** : IND 2 ( Additional Tests: TAN Man )

**AV GROUP NB INC.**  
 103 PINDER ROAD,, NACKAWIC MILL  
 NACKAWIC, NB  
 CA E6G 1W4  
 Contact: Basil Fadulalla  
 basil.fadulalla@adityabirla.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.