




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Area

**Shelter Bay**

Machine Id

**KUBOTA V3800-T K2703 (S/N 2KA2703)**

Component

**Diesel Engine**

Fluid

**MOBIL 15W40 (15 LTR)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>WC0894274</b>	WC0894250	---
Sample Date	Client Info			<b>16 Mar 2024</b>	03 Feb 2024	---
Machine Age	hrs	Client Info		<b>18490</b>	17970	---
Oil Age	hrs	Client Info		<b>520</b>	370	---
Oil Changed	Client Info			<b>Changed</b>	Changed	---
Sample Status				<b>NORMAL</b>	NORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	---
Water	WC Method	>0.2		<b>NEG</b>	NEG	---
Glycol	WC Method			<b>NEG</b>	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>100	<b>7</b>	5	---
Chromium	ppm	ASTM D5185(m)	>20	<b>0</b>	0	---
Nickel	ppm	ASTM D5185(m)	>4	<b>0</b>	<1	---
Titanium	ppm	ASTM D5185(m)		<b>0</b>	0	---
Silver	ppm	ASTM D5185(m)	>3	<b>0</b>	0	---
Aluminum	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	1	---
Lead	ppm	ASTM D5185(m)	>40	<b>0</b>	0	---
Copper	ppm	ASTM D5185(m)	>330	<b>&lt;1</b>	<1	---
Tin	ppm	ASTM D5185(m)	>15	<b>0</b>	0	---
Antimony	ppm	ASTM D5185(m)		<b>0</b>	0	---
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	---
Beryllium	ppm	ASTM D5185(m)		<b>0</b>	0	---
Cadmium	ppm	ASTM D5185(m)		<b>0</b>	0	---





ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<b>2</b>	2	---
Barium	ppm	ASTM D5185(m)		<b>0</b>	0	---
Molybdenum	ppm	ASTM D5185(m)		<b>55</b>	52	---
Manganese	ppm	ASTM D5185(m)		<b>0</b>	0	---
Magnesium	ppm	ASTM D5185(m)		<b>879</b>	837	---
Calcium	ppm	ASTM D5185(m)		<b>1126</b>	1217	---
Phosphorus	ppm	ASTM D5185(m)		<b>955</b>	983	---
Zinc	ppm	ASTM D5185(m)		<b>1157</b>	1138	---
Sulfur	ppm	ASTM D5185(m)		<b>2546</b>	2812	---
Lithium	ppm	ASTM D5185(m)		<b>&lt;1</b>	<1	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>25	<b>2</b>	4	---
Sodium	ppm	ASTM D5185(m)	>118	<b>&lt;1</b>	<1	---
Potassium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	<1	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*	>3	<b>0.2</b>	0.1	---
Nitration	Abs/cm	ASTM D7624*	>20	<b>7.0</b>	6.7	---
Sulfation	Abs./1mm	ASTM D7415*	>30	<b>19.8</b>	19.7	---



# OIL ANALYSIS REPORT











FLUID DEGRADATION	method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	ASTM D7414*	>25	<b>15.1</b>	14.8	---
Base Number (BN)	mg KOH/g	ASTM D2896*		<b>9.85</b>	10.30	---

VISUAL	method	limit/base	current	history1	history2	
Emulsified Water	scalar	Visual*	>0.2	<b>NEG</b>	NEG	---
Free Water	scalar	Visual*		<b>NEG</b>	NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D7279(m)		<b>13.1</b>	13.3	---

## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : WC0894274  
**Lab Number** : 02627249  
**Unique Number** : 5760381  
**Test Package** : MOB 2

**Received** : 08 Apr 2024  
**Tested** : 09 Apr 2024  
**Diagnosed** : 09 Apr 2024 - Wes Davis

**Mowi Canada West**  
 7200 Coho Road  
 Port Hardy, BC  
 CA V0N 2P0  
 Contact: Brian Dalton  
 brian.dalton@mowi.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.