

OIL ANALYSIS REPORT

Sample Rating Trend



Area Chem-Ecol A2404028

Component Unknown Component Fluid CHEM-ECOL PUREPROTECT 68AW (--- GAL)

DIAGNOSIS

Recommendation


We certify that this oil is clean, that the additives are at acceptable levels, and that it is suitable for use.


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Batch #		Client Info		3054-A		
Department		Client Info		Production		
Sample From		Client Info		Machine		
Production Stage		Client Info		Final		
Sent to WC		Client Info		04/05/2024		
Sample Number		Client Info		E30001799		
Sample Date		Client Info		05 Apr 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)		<1		
Chromium	ppm	ASTM D5185(m)		0		
Nickel	ppm	ASTM D5185(m)		0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)		0		
Lead	ppm	ASTM D5185(m)		0		
Copper	ppm	ASTM D5185(m)		<1		
Tin	ppm	ASTM D5185(m)		0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<1		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		107		
Calcium	ppm	ASTM D5185(m)		92		
Phosphorus	ppm	ASTM D5185(m)		426		
Zinc	ppm	ASTM D5185(m)		536		
Sulfur	ppm	ASTM D5185(m)		1054		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	1	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		0		
Sodium	ppm	ASTM D5185(m)		1		
Potassium	ppm	ASTM D5185(m)	>20	<1		
Water	%	ASTM D6304*		0.003		
ppm Water	ppm	ASTM D6304*		26		




OIL ANALYSIS REPORT

FLUID CLEANLINESS









62 Abn 60



Laboratory			
Sample No.			
Lab Numbe			
Unique Numbe			
Test Package			

kpr5/24

Particles >4µm		ASTM D7647	>5000	351		
Particles >6µm		ASTM D7647	>640	93		
Particles >14µm		ASTM D7647	>160	13		
Particles >21µm		ASTM D7647		5		
Particles >38µm		ASTM D7647	>10	2		
Particles >71µm		ASTM D7647	>3	1		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	16/14/11		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.65		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*		NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	68	69.8		
Visc @ 100°C	cSt	ASTM D7279(m)		9.5		
Viscosity Index (VI)	Scale	ASTM D2270*		114		
SAMPLE IMAGES	\$	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Environmental 360 Solutions Ltd. : E30001799 Received : 09 Apr 2024 640 Victoria Street Tested : 10 Apr 2024 : 02627698 Cobourg, ON er er : 5760830 Diagnosed : 11 Apr 2024 - Tatiana Sorkina CA K9A 5H5 : IND 2 (Additional Tests: KF, KV100, PrtCount, TAN Man, VI) Contact: Tatiana Sorkina ae tsorkina@e360s.ca To discuss this sample report, contact Customer Service at 1-905-372-2251. T: (800)263-3939 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied. F: (905)373-4950

Report Id: CHECOB [WCAMIS] 02627698 (Generated: 04/11/2024 09:34:09) Rev: 1

Contact/Location: Tatiana Sorkina - CHECOB

Page 2 of 2