

## **OIL ANALYSIS REPORT**

Sample Rating Trend

ISO

Area IPEX - I01300 Machine Io A2404059

Hydraulic System Fluid AW HYDRAULIC OIL ISO 46 (--- GAL)


Recommendation


The sample submitted is 4 times dirtier than the ISO dirt count recommendation of 19/16/14.


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Batch #		Client Info		Mobile		
Machine ID		Client Info		IMM56		
Department		Client Info		Production		
Sample From		Client Info		Machine		
Production Stage		Client Info		Initial		
Sent to WC		Client Info		04/12/2024		
Sample Number		Client Info		E30001836		
Sample Date		Client Info		10 Apr 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ATTENTION		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	<1		
Chromium	ppm	ASTM D5185(m)	>20	<1		
Nickel	ppm	ASTM D5185(m)	>20	0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>20	0		
Lead	ppm	ASTM D5185(m)	>20	0		
Copper	ppm	ASTM D5185(m)	>20	1		
Tin	ppm	ASTM D5185(m)	>20	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	5	3		
Barium	ppm	ASTM D5185(m)	5	0		
Molybdenum	ppm	ASTM D5185(m)	5	<1		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)	25	9		
Calcium	ppm	ASTM D5185(m)		115		
Phosphorus	ppm	ASTM D5185(m)	300	339		
Zinc	ppm	ASTM D5185(m)		419		
Sulfur	ppm	ASTM D5185(m)	2500	838		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	0		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	0		
Water	%	ASTM D6304*	>0.05	0.003		
ppm Water	ppm	ASTM D6304*	>500	36		



## **OIL ANALYSIS REPORT**








FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	<b>e</b> 16340		
Particles >6µm		ASTM D7647	>1300	485		
Particles >14µm		ASTM D7647	>320	6		
Particles >21µm		ASTM D7647	>80	2		
Particles >38µm		ASTM D7647	>20	1		
Particles >71µm		ASTM D7647	>4	0		
Oil Cleanliness		ISO 4406 (c)	>20/17/15	<b>e</b> 21/16/10		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.57	0.29		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.05	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	46	42.7		
Visc @ 100°C	cSt	ASTM D7279(m)	6.7	7.0		
Viscosity Index (VI)	Scale	ASTM D2270*	97	123		
SAMPLE IMAGES	3	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image





Report Id: CHECOB [WCAMIS] 02628861 (Generated: 04/17/2024 15:13:04) Rev: 1

Contact/Location: Tatiana Sorkina - CHECOB Page 2 of 2