

OIL ANALYSIS REPORT

Sample Rating Trend





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.


Fluid Condition

The condition of the fluid is acceptable for the time in service.

SAMPLE INFORM		method	limit/base	current	history1	history2
		Client Info	innivoase	WC0890702		
Sample Number Sample Date		Client Info		20 Dec 2023		
Machine Age	hrs	Client Info		20 Dec 2023 91019		
Oil Age	hrs	Client Info		26756		
Oil Changed	1115	Client Info		Changed		
Sample Status		Client Into		NORMAL		
				NOTIMAL		
CONTAMINATION	١	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>200	120		
Chromium	ppm	ASTM D5185(m)	>5	<1		
Nickel	ppm	ASTM D5185(m)	>5	0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)	>7	0		
Aluminum	ppm	ASTM D5185(m)	>25	16		
Lead	ppm	ASTM D5185(m)	>45	0		
Copper	ppm	ASTM D5185(m)	>225	18		
Tin	ppm	ASTM D5185(m)	>10	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		289		
Barium	ppm	ASTM D5185(m)		4		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		2		
Magnesium	ppm	ASTM D5185(m)		243		
Calcium	ppm	ASTM D5185(m)		429		
Phosphorus	ppm	ASTM D5185(m)		3		
Zinc	ppm	ASTM D5185(m)		355		
Sulfur	ppm	ASTM D5185(m)		843		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>125	18		
Sodium	ppm	ASTM D5185(m)		2		
Potassium	ppm	ASTM D5185(m)	>20	1		



OIL ANALYSIS REPORT



	VISUAL		method	limit/base	current	history1	history2	
	White Metal	scalar	Visual*	NONE	NONE			
	Yellow Metal	scalar	Visual*	NONE	NONE			
1	Precipitate	scalar	Visual*	NONE	NONE			
	Silt	scalar	Visual*	NONE	NONE			
	Debris	scalar	Visual*	NONE	NONE			
	Sand/Dirt	scalar	Visual*	NONE	NONE			
Dec20/23	Appearance Odor	scalar	Visual* Visual*	NORML				
	Emulsified Water	scalar scalar	Visual*	NORML	NEG			
	Free Water	scalar	Visual*	>0.1	NEG			
	FLUID PROPER		method	limit/base	current	history1	history2	
	Visc @ 40°C	cSt	ASTM D7279(m)	minubacc	20.0			
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2	
	Color					no image	no image	
	Bottom					no image	no image	
	GRAPHS Iron (ppm)				Lead (ppm)			
	400 Severe			100	Severe		1	
	E 200 - Abnormal			- 튭 50	Abnormal o			
	Dec20/23			Dec20/23 +	Dec20/23		Dec20/23 +	
	Aluminum (ppm)			15	Chromium (ppm)			
	60 Severe	Severe			Sminn		1	
				E ¹⁰	Abnormal			
	0							
	Dec20/23			Dec20/23	Dec20/23		Dec20/23	
				De			De	
	Copper (ppm)			300	Silicon (ppm)			
	Severe							
	E 400 - Abnormal			툴 ²⁰⁰ 100	Abnormal			
	Dec20/23			Dec20/23	Dec20/23		Dec20/23	
				Dec			Dec	
	Viscosity @ 40°C			600	Additives			
	150 - Abnormal 유명하여배례 승만 50			€ ⁴⁰⁰	calcium		****	
	४) 50-			특 ⁴⁰⁰ 문 ₂₀₀	· · · · · · · · · · · · · · · · · · ·			
	10			O	L.p	******	23	
	Dec20/23			Dec20/23	Dec20/23		Dec20/23	
Laboratory Sample No. Lab Number	: WC0890702	Rece Teste	•			488 Sco	Ken Purtor 488 Scotchmere Cour Waterloo, OI CA N2K 3E Contact: Ken Purto purtonk@gmail.cor T	

Report Id: KEN488WAT [WCAMIS] 02628907 (Generated: 04/16/2024 10:42:56) Rev: 1

Contact/Location: Ken Purton - KEN488WAT Page 2 of 2