




# OIL ANALYSIS REPORT

## Sample Rating Trend



ISO



Area

**MAXI PAYSAGE [02548846]**

Machine Id

**HITACHI ZX135US-6 EX2004 (S/N HCMDA550T00513365)**

Component

**Hydraulic System**

Fluid

**PANOLIN HLP SYNTH 46 (185 LTR)**

### DIAGNOSIS

#### Recommendation

Nous recommandons le remplacement des filtres de ce composant. Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition.

#### Wear

Les taux d'usure de tous les composants sont normaux.

#### Contamination

Il y a une légère quantité de limon (particules de 4 à 14 microns) dans l'huile. Il y a une faible concentration (<5.0%) d'huile minérale présente dans le fluide. La teneur en eau est négligeable.

#### Fluid Condition

Le AN est acceptable pour ce fluide. L'état de l'huile permet d'en prolonger l'utilisation.

### SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>WC</b>	WC	---
Sample Date	Client Info		<b>09 Apr 2024</b>	18 Dec 2023	---
Machine Age	hrs	Client Info	<b>2857</b>	2725	---
Oil Age	hrs	Client Info	<b>0</b>	0	---
Oil Changed	Client Info		<b>N/A</b>	N/A	---
Sample Status			<b>ATTENTION</b>	ABNORMAL	---

### WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	<b>1</b>	2
Chromium	ppm	ASTM D5185(m)	>10	<b>&lt;1</b>	<1
Nickel	ppm	ASTM D5185(m)	>10	<b>0</b>	<1
Titanium	ppm	ASTM D5185(m)		<b>&lt;1</b>	0
Silver	ppm	ASTM D5185(m)		<b>0</b>	0
Aluminum	ppm	ASTM D5185(m)	>10	<b>0</b>	<1
Lead	ppm	ASTM D5185(m)	>10	<b>0</b>	<1
Copper	ppm	ASTM D5185(m)	>75	<b>&lt;1</b>	1
Tin	ppm	ASTM D5185(m)	>10	<b>0</b>	0
Antimony	ppm	ASTM D5185(m)		<b>0</b>	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0
Beryllium	ppm	ASTM D5185(m)		<b>0</b>	0
Cadmium	ppm	ASTM D5185(m)		<b>0</b>	0

### ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	0	<b>&lt;1</b>	<1
Barium	ppm	ASTM D5185(m)	0	<b>0</b>	0
Molybdenum	ppm	ASTM D5185(m)	0	<b>0</b>	0
Manganese	ppm	ASTM D5185(m)	0	<b>0</b>	0
Magnesium	ppm	ASTM D5185(m)	0	<b>&lt;1</b>	<1
Calcium	ppm	ASTM D5185(m)	0	<b>3</b>	15
Phosphorus	ppm	ASTM D5185(m)	1700	<b>1476</b>	1455
Zinc	ppm	ASTM D5185(m)	0	<b>16</b>	29
Sulfur	ppm	ASTM D5185(m)	1350	<b>1288</b>	1418
Lithium	ppm	ASTM D5185(m)		<b>&lt;1</b>	<1

### CONTAMINANTS






	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>20	<b>2</b>	2
Sodium	ppm	ASTM D5185(m)		<b>&lt;1</b>	1
Potassium	ppm	ASTM D5185(m)	>20	<b>0</b>	<1
Water	%	ASTM D6304*	>0.05	<b>0.019</b>	0.018
ppm Water	ppm	ASTM D6304*	>500	<b>192</b>	184

### INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*		<b>0</b>	0
Nitration	Abs/cm	ASTM D7624*		<b>3.7</b>	3.7
Sulfation	Abs/.1mm	ASTM D7415*		<b>158.2</b>	135.9
Mineral Oil Content	%	ASTM D7418*	<5.0%	<b>&lt;5.0</b>	8.9



# OIL ANALYSIS REPORT



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : WC  
**Lab Number** : 02629076  
**Unique Number** : 5762208  
**Test Package** : MOB 2 ( Additional Tests: TAN Man )

**Received** : 15 Apr 2024  
**Tested** : 17 Apr 2024  
**Diagnosed** : 22 Apr 2024 - Bill Quesnel

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.

**Envirolin Canada**  
 520 rue Adanac  
 Quebec, QC  
 CA G1C 7B7  
 Contact: Patrick Levesque  
 patrick.levesque@envirolin.com  
 T: (418)623-1216  
 F: (418)660-8889


FLUID CLEANLINESS	method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647	>2500	● 2778	▲ 10334	---
Particles >6µm	ASTM D7647	>640	● 366	▲ 2422	---
Particles >14µm	ASTM D7647	>80	● 9	● 132	---
Particles >21µm	ASTM D7647	>20	● 3	28	---
Particles >38µm	ASTM D7647	>4	● 1	2	---
Particles >71µm	ASTM D7647	>3	● 0	1	---
Oil Cleanliness	ISO 4406 (c)	>18/16/13	● 19/16/10	▲ 21/18/14	---

FLUID DEGRADATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	ASTM D7414*	145.6	134.8	---
Acid Number (AN)	mg KOH/g	ASTM D974*	0.51	0.55	---

VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	---
Yellow Metal	scalar	Visual*	NONE	NONE	---
Precipitate	scalar	Visual*	NONE	NONE	---
Silt	scalar	Visual*	NONE	NONE	---
Debris	scalar	Visual*	NONE	NONE	---
Sand/Dirt	scalar	Visual*	NONE	NONE	---
Appearance	scalar	Visual*	NORML	NORML	---
Odor	scalar	Visual*	NORML	NORML	---
Emulsified Water	scalar	Visual*	NEG	NEG	---
Free Water	scalar	Visual*	NEG	NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	47.0	46.1	---
Visc @ 100°C	cSt	ASTM D7279(m)	8.1	8.1	---
Viscosity Index (VI)	Scale	ASTM D2270*	146	149	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color					no image
Bottom					no image





# MINERAL OIL CONTENT REPORT

PASS



Area

**MAXI PAYSAGE [02548846]**

Machine Id

**HITACHI ZX135US-6 EX2004 (S/N HCMDA550T00513365)**

Component

**Hydraulic System**


Fluid

**PANOLIN HLP SYNTH 46 (185 LTR)**


## SPECTRAL ANALYSIS

		method	limit/base	current	history1	history2
Zinc	ppm	ASTM D5185(m)	0	<b>16</b>	● 29	---
Mineral Oil Content	%	ASTM D7418*	<5.0%	<b>&lt;5.0</b>	▲ 8.9	---


FT-IR - Esters I



FT-IR - Esters II



FT-IR Spectrum (Absorbance)



ISO 17025:2017  
Accredited  
Laboratory

**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : WC  
**Lab Number** : 02629076  
**Unique Number** : 5762208  
**Test Package** : MOB 2 ( Additional Tests: TAN Man )

**Received** : 15 Apr 2024  
**Tested** : 17 Apr 2024  
**Diagnosed** : 22 Apr 2024 - Bill Quesnel

To discuss this sample report, contact Customer Service at 1-800-268-2131.

Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

Validity of results and interpretation are based on the sample and information as supplied.

### EnviroLin Canada

520 rue Adanac  
Quebec, QC  
CA G1C 7B7

Contact: Patrick Levesque  
patrick.levesque@envirolin.com

T: (418)623-1216  
F: (418)660-8889

*This page left intentionally blank*