

OIL ANALYSIS REPORT

Sample Rating Trend

ISO

Area Metelix - M10200 AG300

Hydraulic System Fluid AW HYDRAULIC OIL ISO 46 (--- GAL)

DIAGNOSIS


Recommendation


The sample submitted is 2 times dirtier than the ISO dirt count recommendation of 19/16/14.


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Machine ID		Client Info		Machine 8206		
Department		Client Info		Sales		
Sample From		Client Info		Machine		
Production Stage		Client Info		Initial		
Sent to WC		Client Info		04/15/2024		
Sample Number		Client Info		E30001862		
Sample Date		Client Info		03 Apr 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ATTENTION		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	2		
Chromium	ppm	ASTM D5185(m)	>20	0		
Nickel	ppm	ASTM D5185(m)	>20	0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>20	0		
Lead	ppm	ASTM D5185(m)	>20	0		
Copper	ppm	ASTM D5185(m)	>20	3		
Tin	ppm	ASTM D5185(m)	>20	0		
Antimony	ppm	ASTM D5185(m)		2		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	5	0		
Barium	ppm	ASTM D5185(m)	5	0		
Molybdenum	ppm	ASTM D5185(m)	5	0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)	25	<1		
Calcium	ppm	ASTM D5185(m)	200	57		
Phosphorus	ppm	ASTM D5185(m)	300	337		
Zinc	ppm	ASTM D5185(m)	370	414		
Sulfur	ppm	ASTM D5185(m)	2500	2948		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	0		
Sodium	ppm	ASTM D5185(m)		<1		
Potassium	ppm	ASTM D5185(m)	>20	<1		
Water	%	ASTM D6304*	>0.05	0.001		
ppm Water	ppm	ASTM D6304*	>500	12		



OIL ANALYSIS REPORT









FLUID CLEANLIN		method	limit/base	ourropt	history	biotor
	IESS			current	history1	history
Particles >4µm		ASTM D7647	>5000	6685		
Particles >6µm		ASTM D7647		<mark> </mark> 1256		
Particles >14µm		ASTM D7647	>160	64		
Particles >21µm		ASTM D7647		16		
Particles >38µm		ASTM D7647	>10	2		
Particles >71µm		ASTM D7647		1		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	e 20/17/13		
FLUID DEGRADA	TION	method	limit/base	current	history1	history
Acid Number (AN)	mg KOH/g	ASTM D974*	0.57	0.28		
VISUAL		method	limit/base	current	history1	history
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.05	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history
Visc @ 40°C	cSt	ASTM D7279(m)	46	50.7		
Visc @ 100°C	cSt	ASTM D7279(m)	6.7	7.3		
Viscosity Index (VI)	Scale	ASTM D2270*	97	103		
SAMPLE IMAGES	3	method	limit/base	current	history1	history
Color					no image	no image



: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Environmental 360 Solutions Ltd. : E30001862 Sample No. Received : 17 Apr 2024 640 Victoria Street Lab Number : 02629603 Tested : 18 Apr 2024 Cobourg, ON Unique Number : 5762735 Diagnosed : 22 Apr 2024 - Tatiana Sorkina CA K9A 5H5 Test Package : IND 2 (Additional Tests: KF, KV100, VI) Contact: Tatiana Sorkina tsorkina@e360s.ca To discuss this sample report, contact Customer Service at 1-905-372-2251. T: (800)263-3939 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied. F: (905)373-4950

Bottom

Report Id: CHECOB [WCAMIS] 02629603 (Generated: 04/22/2024 11:29:21) Rev: 1

Contact/Location: Tatiana Sorkina - CHECOB

no image

no image

Page 2 of 2