

## **OIL ANALYSIS REPORT**

Sample Rating Trend



### Machine Id QC240415IND2

Hydraulic System Fluid AW HYDRAULIC OIL ISO 68 (--- GAL)

#### DIAGNOSIS

#### Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The water content is negligible. The system and fluid cleanliness is acceptable.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0932942	WC0932939	WC0932938
Sample Date		Client Info		22 Apr 2024	19 Apr 2024	18 Apr 2024
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	0	0	0
Chromium	ppm	ASTM D5185(m)	>20	0	0	0
Nickel	ppm	ASTM D5185(m)	>20	0	0	0
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)		0	0	0
Aluminum	ppm	ASTM D5185(m)	>20	0	0	0
Lead	ppm	ASTM D5185(m)	>20	0	0	0
Copper	ppm	ASTM D5185(m)		0	0	0
Tin	ppm	ASTM D5185(m)	>20	0	0	0
Antimony	ppm	ASTM D5185(m)		0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	5	0	0	0
Barium	ppm	ASTM D5185(m)	5	0	0	0
Molybdenum	ppm	ASTM D5185(m)	5	0	0	0
Manganese	ppm	ASTM D5185(m)		0	0	0
Magnesium	ppm	ASTM D5185(m)	25	<1	0	<1
Calcium	ppm	ASTM D5185(m)	200	47	46	46
Phosphorus	ppm	ASTM D5185(m)	300	232	227	227
Zinc	ppm	ASTM D5185(m)	370	293	292	292
Sulfur	ppm	ASTM D5185(m)	2500	5151	5068	5130
Lithium	ppm	ASTM D5185(m)		<1	<1	<1
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	0	0	0
Sodium	ppm	ASTM D5185(m)		0	0	0
Potassium	ppm	ASTM D5185(m)	>20	0	<1	0
Water	%	ASTM D6304*	>0.05	0.002	0.002	0.001
ppm Water	ppm	ASTM D6304*	>500	18	23	15
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	348	288	322
Particles >6µm		ASTM D7647	>1300	94	66	83
Particles >14µm		ASTM D7647	>160	5	6	9
Particles >21µm		ASTM D7647	>40	2	3	4
Particles >38µm		ASTM D7647	>10	0	1	2
Particles >71µm		ASTM D7647	>3	0	1	1

16/14/10

15/13/10

ISO 4406 (c) >19/17/14

**Oil Cleanliness** 

16/14/10




# **OIL ANALYSIS REPORT**

		150		Labo	
	Apr15/2 <sup>4</sup>	Apr17/24	Apr18/24	Apr19/24	Apr22/24
60· 55·	Abnormal	4	+	+	
- 07 - 07 - 07 - 07 - 07 - 07 - 07 - 07					
	Base				
80 · 75 ·	Abnormal				
	Viscosity @		-	-	
5.	Apr15/24	Apr17/24 -	Apr18/24 -	Apr19/24 -	Apr22/24 -
7. 6.					
cSt (100°C)	Abnormal				
	Bace				
11- 10-	Abnormal		1	<del>-</del>	
	⊲ Viscosity @			4	4
Ū.	Apr15/24	Apr17/24 -	Apr18/24 .	Apr19/24 -	pr22/24
1000 · 0 ·	Abnormal				
≥ 2000. 2000					
(bdd) 3000 - Mater 3000 - 2000					
6000+ 5000+	Severe				
0000	Water (KF)	)			
	Apr15/24	Apr17/24	Apr18/24	Apr19/24	Apr22/24
0.20 P	- 0				
aquing 0.40	Abaamal				
Acid Number (mg KOH/g) 0.60 0.40 0.40	Base				
1.00-					
0.4	Acid Numb	14µ er	21µ	38µ	71µ
2.			-		-8
120 30 8					-14 -12 -10
1,920 · 480 ·					-20 0 -18 0 -16 0 -14 10 -12 0
	Abnormal	~			-20
30,720					-22 8

FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.57	0.24	0.25	0.27
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.05	NEG	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	68	67.9	67.9	68.1
Visc @ 100°C	cSt	ASTM D7279(m)	8.6	8.7	8.8	8.8
Viscosity Index (VI)	Scale	ASTM D2270*	96	99	101	101
SAMPLE IMAGES	\$	method	limit/base	current	history1	history2
						ease the

Color

Bottom



: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 WearCheck Quality Control Sample Results : WC0932942 Received : 22 Apr 2024 : 02630585 Tested : 24 Apr 2024 Burlington, ON 17025:201 Accredited Laboratory Unique Number : 5763717 Diagnosed : 24 Apr 2024 - Kevin Marson CA Test Package : IND 2 ( Additional Tests: KF, KV100, VI ) Contact: Dorian Anderson To discuss this sample report, contact Customer Service at 1-800-268-2131. dorian.anderson@wearcheck.com Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab. T: (289)291-4652 Validity of results and interpretation are based on the sample and information as supplied. F: (905)569-8605

Report Id: QA [WCAMIS] 02630585 (Generated: 04/24/2024 08:54:06) Rev: 1