

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Societe Via - A15100 A2406054

Hydraulic System

AW HYDRAULIC OIL ISO 46 (--- GAL)



| | | | | Jun 2024 | | |
|------------------|--------|---------------|------------|--------------|----------|----------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Batch # | | Client Info | | 2024 05 0890 | | |
| Department | | Client Info | | Production | | |
| Sample From | | Client Info | | Machine | | |
| Production Stage | | Client Info | | Initial | | |
| Sent to WC | | Client Info | | 06/06/2024 | | |
| Sample Number | | Client Info | | E30002338 | | |
| Sample Date | | Client Info | | 06 Jun 2024 | | |
| Machine Age | hrs | Client Info | | 0 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATION | V | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.05 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185(m) | >20 | 9 | | |
| Chromium | ppm | ASTM D5185(m) | >10 | 3 | | |
| Nickel | ppm | ASTM D5185(m) | >10 | 0 | | |
| Titanium | ppm | ASTM D5185(m) | | <1 | | |
| Silver | ppm | ASTM D5185(m) | | 0 | | |
| Aluminum | ppm | ASTM D5185(m) | >10 | 2 | | |
| Lead | ppm | ASTM D5185(m) | >20 | 0 | | |
| Copper | ppm | ASTM D5185(m) | >20 | 2 | | |
| Tin | ppm | ASTM D5185(m) | >10 | 0 | | |
| Antimony | ppm | ASTM D5185(m) | | 0 | | |
| Vanadium | ppm | ASTM D5185(m) | | 0 | | |
| Beryllium | ppm | ASTM D5185(m) | | 0 | | |
| Cadmium | ppm | ASTM D5185(m) | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185(m) | 5 | 18 | | |
| Barium | ppm | ASTM D5185(m) | 5 | 0 | | |
| Molybdenum | ppm | ASTM D5185(m) | 5 | 10 | | |
| Manganese | ppm | ASTM D5185(m) | | 0 | | |
| Magnesium | ppm | ASTM D5185(m) | 25 | 160 | | |
| Calcium | ppm | ASTM D5185(m) | 200 | 375 | | |
| Phosphorus | ppm | ASTM D5185(m) | 300 | 495 | | |
| Zinc | ppm | ASTM D5185(m) | 370 | 563 | | |
| Sulfur | ppm | ASTM D5185(m) | 2500 | 1642 | | |
| Lithium | ppm | ASTM D5185(m) | | <1 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185(m) | >15 | 9 | | |
| Sodium | ppm | ASTM D5185(m) | | 4 | | |
| Potassium | ppm | ASTM D5185(m) | >20 | 1 | | |



OIL ANALYSIS REPORT

| VISUAL | | method | limit/base | current | history1 | history2 |
|---------------------|--------|---------|------------|---------|----------|----------|
| White Metal | scalar | Visual* | NONE | NONE | | |
| Yellow Metal | scalar | Visual* | NONE | NONE | | |
| Precipitate | scalar | Visual* | NONE | NONE | | |
| Silt | scalar | Visual* | NONE | NONE | | |
| Debris | scalar | Visual* | NONE | NONE | | |
| Sand/Dirt | scalar | Visual* | NONE | NONE | | |
| Appearance | scalar | Visual* | NORML | NORML | | |
| Odor | scalar | Visual* | NORML | NORML | | |
| | | | | | | |
| SAMPLE IMAGES | | method | | | | history2 |
| SAMPLE IMAGES Color | \$ | method | limit/base | current | no image | no image |
| | | method | limit/base | current | | |
| Color | | method | limit/base | current | no image | no image |



CALA ISO 17025:2017 Accredited Laboratory

Laboratory

Sample No. : E30002338 Lab Number : 02640941 $\textbf{Unique Number} \hspace{0.1cm} : 5798480$

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9

Received Tested Diagnosed

: 10 Jun 2024 : 11 Jun 2024

: 11 Jun 2024 - Tatiana Sorkina

Cobourg, ON CA K9A 5H5 Contact: Tatiana Sorkina tsorkina@e360s.ca

Environmental 360 Solutions Ltd.

T: (800)263-3939 F: (905)373-4950

640 Victoria Street

Test Package : TEST (Additional Tests: ICP) To discuss this sample report, contact Customer Service at 1-905-372-2251.

Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.