

## **OIL ANALYSIS REPORT**

### Area City of Windsor Transfer Station - 888092 RB016

Component Unknown Component Fluid MOBIL DTE 10 EXCEL 46 (--- GAL)

#### DIAGNOSIS

#### Recommendation

The sample submitted is 2 times dirtier than the ISO dirt count recommendation of 19/16/14.

#### Contamination

Particles  $>4\mu$ m and oil cleanliness are notably high.


SAMPLE INFORM	<b>IATION</b>					
Machine ID		Client Info		South Push Pit		
Department		Client Info		Sales		
Sample From		Client Info		Machine		
Production Stage		Client Info		Initial		
Sent to WC		Client Info		06/07/2024		
Sample Number		Client Info		E30002349		
Sample Date		Client Info		04 May 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ATTENTION		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)		2		
Chromium	ppm	ASTM D5185(m)		3		
Nickel	ppm	ASTM D5185(m)		0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)		0		
Lead	ppm	ASTM D5185(m)		0		
Copper	ppm	ASTM D5185(m)		<1		
Tin	ppm	ASTM D5185(m)		0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		0		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		1		
Calcium	ppm	ASTM D5185(m)		73		
Phosphorus	ppm	ASTM D5185(m)		403		
Zinc	ppm	ASTM D5185(m)		69		
Sulfur	ppm	ASTM D5185(m)		1134		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		0		
Sodium	ppm	ASTM D5185(m)		<1		
Potassium	ppm	ASTM D5185(m)	>20	<1		
Water	%	ASTM D6304*		0.008		
ppm Water	ppm	ASTM D6304*		88		


Sample Rating Trend


ISO



# **OIL ANALYSIS REPORT**








FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	9306		
Particles >6µm		ASTM D7647	>640	615		
Particles >14µm		ASTM D7647	>160	6		
Particles >21µm		ASTM D7647	>40	2		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	<b>0/16/10</b>		
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.07		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*		NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	TIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	45.6	44.9		
Visc @ 100°C	cSt	ASTM D7279(m)	8.5	8.0		
Viscosity Index (VI)	Scale	ASTM D2270*	164	151		
SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Color					no image	no image

Bottom



Report Id: CHECOB [WCAMIS] 02641113 (Generated: 06/13/2024 13:43:56) Rev: 1

Contact/Location: Tatiana Sorkina - CHECOB

no image

no image