


PROBLEM SUMMARY


Area
IMT Corporation - I02600
 Machine Id
AM1012
 Component
Quench Oil
 Fluid
{not provided} (--- GAL)

Sample Rating Trend




COMPONENT CONDITION SUMMARY

▲ Particle Trend



● Ferrous Alloys



RECOMMENDATION

The sample submitted is 128 times dirtier than the ISO dirt count recommendation of 19/16/14.

PROBLEMATIC TEST RESULTS

Sample Status			SEVERE	---	---
Particles >4µm	ASTM D7647	>5000	▲ 376403	---	---
Particles >6µm	ASTM D7647	>640	▲ 121114	---	---
Particles >14µm	ASTM D7647	>160	▲ 464	---	---
Oil Cleanliness	ISO 4406 (c)	>19/16/14	▲ 26/24/16	---	---

Customer Id: CHECOB
 Sample No.: E30002341
 Lab Number: 02641117
 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data:

Tatiana Sorkina +1 (800)263-3939
tsorkina@e360s.ca

To change component or sample information:

Gloria Gonzalez +1 (289)291-4643 x4643
gloria.gonzalez@wearcheck.com

RECOMMENDED ACTIONS


There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS



OIL ANALYSIS REPORT

Sample Rating Trend



Area
IMT Corporation - I02600
 Machine Id
AM1012
 Component
Quench Oil
 Fluid
{not provided} (--- GAL)

DIAGNOSIS

- ▲ **Recommendation**
 The sample submitted is 128 times dirtier than the ISO dirt count recommendation of 19/16/14.
- **Wear**
 Iron ppm levels are noted.
- ▲ **Contamination**
 Particles >6µm are severely high. Particles >4µm are severely high. Oil Cleanliness are severely high. Particles >14µm are abnormally high.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Machine ID	Client Info		Furnace #1535	---	---
Department	Client Info		Sales	---	---
Sample From	Client Info		Machine	---	---
Production Stage	Client Info		Initial	---	---
Sent to WC	Client Info		06/06/2024	---	---
Sample Number	Client Info		E30002341	---	---
Sample Date	Client Info		28 May 2024	---	---
Machine Age	hrs	Client Info	0	---	---
Oil Age	hrs	Client Info	0	---	---
Oil Changed		Client Info	N/A	---	---
Sample Status			SEVERE	---	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	● 19	---	---
Chromium	ppm	ASTM D5185(m)	1	---	---
Nickel	ppm	ASTM D5185(m)	<1	---	---
Titanium	ppm	ASTM D5185(m)	0	---	---
Silver	ppm	ASTM D5185(m)	0	---	---
Aluminum	ppm	ASTM D5185(m)	<1	---	---
Lead	ppm	ASTM D5185(m)	0	---	---
Copper	ppm	ASTM D5185(m)	3	---	---
Tin	ppm	ASTM D5185(m)	0	---	---
Antimony	ppm	ASTM D5185(m)	0	---	---
Vanadium	ppm	ASTM D5185(m)	0	---	---
Beryllium	ppm	ASTM D5185(m)	0	---	---
Cadmium	ppm	ASTM D5185(m)	0	---	---






ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	1	---	---
Barium	ppm	ASTM D5185(m)	0	---	---
Molybdenum	ppm	ASTM D5185(m)	0	---	---
Manganese	ppm	ASTM D5185(m)	<1	---	---
Magnesium	ppm	ASTM D5185(m)	<1	---	---
Calcium	ppm	ASTM D5185(m)	17	---	---
Phosphorus	ppm	ASTM D5185(m)	5	---	---
Zinc	ppm	ASTM D5185(m)	12	---	---
Sulfur	ppm	ASTM D5185(m)	313	---	---
Lithium	ppm	ASTM D5185(m)	<1	---	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	0	---	---
Sodium	ppm	ASTM D5185(m)	2	---	---
Potassium	ppm	ASTM D5185(m) >20	2	---	---
Water	%	ASTM D6304*	0.003	---	---
ppm Water	ppm	ASTM D6304*	32	---	---

OIL ANALYSIS REPORT



FLUID CLEANLINESS	method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647	>5000	▲ 376403	---	---
Particles >6µm	ASTM D7647	>640	▲ 121114	---	---
Particles >14µm	ASTM D7647	>160	▲ 464	---	---
Particles >21µm	ASTM D7647	>40	21	---	---
Particles >38µm	ASTM D7647	>10	0	---	---
Particles >71µm	ASTM D7647	>3	0	---	---
Oil Cleanliness	ISO 4406 (c)	>19/16/14	▲ 26/24/16	---	---

FLUID DEGRADATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.28	---	---

VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	---	---
Yellow Metal	scalar	Visual*	NONE	---	---
Precipitate	scalar	Visual*	NONE	---	---
Silt	scalar	Visual*	NONE	---	---
Debris	scalar	Visual*	NONE	---	---
Sand/Dirt	scalar	Visual*	NONE	---	---
Appearance	scalar	Visual*	NORML	---	---
Odor	scalar	Visual*	NORML	---	---
Emulsified Water	scalar	Visual*	NEG	---	---
Free Water	scalar	Visual*	NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	16.7	---	---
Visc @ 100°C	cSt	ASTM D7279(m)	3.7	---	---
Viscosity Index (VI)	Scale	ASTM D2270*	107	---	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color				no image	no image
Bottom				no image	no image



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : E30002341
Lab Number : 02641117
Unique Number : 5798656
Test Package : IND 2 (Additional Tests: KF, KV100, PrtCount, TAN Man, VI)

Environmental 360 Solutions Ltd.
 640 Victoria Street
 Cobourg, ON
 CA K9A 5H5
 Contact: Tatiana Sorkina
 tsorkina@e360s.ca
 T: (800)263-3939
 F: (905)373-4950

To discuss this sample report, contact Customer Service at 1-905-372-2251.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.