



# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Area  
**Vicinity Energy - 888095**  
 Machine Id  
**FK420-RC**  
 Component  
**Unknown Component**  
 Fluid  
**CHEVRON DELO 710 LE (--- GAL)**

## DIAGNOSIS

### Recommendation

We certify this oil to be clean and dry.

### Contamination

Particles >4µm and oil cleanliness are notably high.

### Fluid Condition

Sodium ppm levels are notably high.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Machine ID	Client Info		<b>Engine Oil Pan</b>	---	---
Department	Client Info		<b>Sales</b>	---	---
Sample From	Client Info		<b>Machine</b>	---	---
Production Stage	Client Info		<b>Lab Reclaim</b>	---	---
Sent to WC	Client Info		<b>06/10/2024</b>	---	---
Sample Number	Client Info		<b>E30002363</b>	---	---
Sample Date	Client Info		<b>10 Jun 2024</b>	---	---
Machine Age	hrs	Client Info	<b>0</b>	---	---
Oil Age	hrs	Client Info	<b>0</b>	---	---
Oil Changed		Client Info	<b>N/A</b>	---	---
Sample Status			<b>NORMAL</b>	---	---

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	<b>5</b>	---	---
Chromium	ppm	ASTM D5185(m)	<b>4</b>	---	---
Nickel	ppm	ASTM D5185(m)	<b>0</b>	---	---
Titanium	ppm	ASTM D5185(m)	<b>0</b>	---	---
Silver	ppm	ASTM D5185(m)	<b>0</b>	---	---
Aluminum	ppm	ASTM D5185(m)	<b>2</b>	---	---
Lead	ppm	ASTM D5185(m)	<b>2</b>	---	---
Copper	ppm	ASTM D5185(m)	<b>1</b>	---	---
Tin	ppm	ASTM D5185(m)	<b>0</b>	---	---
Antimony	ppm	ASTM D5185(m)	<b>0</b>	---	---
Vanadium	ppm	ASTM D5185(m)	<b>0</b>	---	---
Beryllium	ppm	ASTM D5185(m)	<b>0</b>	---	---
Cadmium	ppm	ASTM D5185(m)	<b>0</b>	---	---






## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	<b>30</b>	---	---
Barium	ppm	ASTM D5185(m)	<b>&lt;1</b>	---	---
Molybdenum	ppm	ASTM D5185(m)	<b>42</b>	---	---
Manganese	ppm	ASTM D5185(m)	<b>&lt;1</b>	---	---
Magnesium	ppm	ASTM D5185(m)	<b>33</b>	---	---
Calcium	ppm	ASTM D5185(m)	<b>2795</b>	---	---
Phosphorus	ppm	ASTM D5185(m)	<b>17</b>	---	---
Zinc	ppm	ASTM D5185(m) 10	<b>21</b>	---	---
Sulfur	ppm	ASTM D5185(m)	<b>1759</b>	---	---
Lithium	ppm	ASTM D5185(m)	<b>&lt;1</b>	---	---

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	<b>4</b>	---	---
Sodium	ppm	ASTM D5185(m)	<b>439</b>	---	---
Potassium	ppm	ASTM D5185(m) >20	<b>6</b>	---	---
Water	%	ASTM D6304*	<b>0.034</b>	---	---
ppm Water	ppm	ASTM D6304*	<b>349</b>	---	---

# OIL ANALYSIS REPORT



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : E30002363  
**Lab Number** : **02641408**  
**Unique Number** : 5798947  
**Test Package** : IND 2 ( Additional Tests: KF, KV100, PrtCount, VI )

**Environmental 360 Solutions Ltd.**  
 640 Victoria Street  
 Cobourg, ON  
 CA K9A 5H5  
 Contact: Tatiana Sorkina  
 tsorkina@e360s.ca  
 T: (800)263-3939  
 F: (905)373-4950

To discuss this sample report, contact Customer Service at 1-905-372-2251.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.

FLUID CLEANLINESS	method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647	>5000	<b>5359</b>	---	---
Particles >6µm	ASTM D7647	>640	<b>70</b>	---	---
Particles >14µm	ASTM D7647	>160	<b>4</b>	---	---
Particles >21µm	ASTM D7647	>40	<b>2</b>	---	---
Particles >38µm	ASTM D7647	>10	<b>0</b>	---	---
Particles >71µm	ASTM D7647	>3	<b>0</b>	---	---
Oil Cleanliness	ISO 4406 (c)	>19/16/14	<b>20/13/9</b>	---	---

FLUID DEGRADATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	<b>0.34</b>	---	---

VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	<b>NONE</b>	---
Yellow Metal	scalar	Visual*	NONE	<b>NONE</b>	---
Precipitate	scalar	Visual*	NONE	<b>NONE</b>	---
Silt	scalar	Visual*	NONE	<b>NONE</b>	---
Debris	scalar	Visual*	NONE	<b>NONE</b>	---
Sand/Dirt	scalar	Visual*	NONE	<b>NONE</b>	---
Appearance	scalar	Visual*	NORML	<b>NORML</b>	---
Odor	scalar	Visual*	NORML	<b>NORML</b>	---
Emulsified Water	scalar	Visual*	<b>NEG</b>	---	---
Free Water	scalar	Visual*	<b>NEG</b>	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	136.4	<b>128</b>	---
Visc @ 100°C	cSt	ASTM D7279(m)	15.5	<b>14.0</b>	---
Viscosity Index (VI)	Scale	ASTM D2270*	117	<b>107</b>	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color				no image	no image
Bottom				no image	no image