

## **OIL ANALYSIS REPORT**

Sample Rating Trend



### Area Ipex - 101300 RB006-R

Heat Transfer Fluid

#### PETRO CANADA PURITY FG HEAT TRANSFER FLUID (--- GAL)

#### DIAGNOSIS


**Recommendation** We certify this oil to be clean and dry.


SAMPLE INFORM	<b>NATION</b>	method	limit/base	current	history1	history2
Machine ID		Client Info		Pail		
Department		Client Info		Sales		
Sample From		Client Info		Machine		
Production Stage		Client Info		Lab Reclaim		
Sent to WC		Client Info		06/11/2024		
Sample Number		Client Info		E30002366		
Sample Date		Client Info		11 Jun 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>200	9		
Chromium	ppm	ASTM D5185(m)	>21	0		
Nickel	ppm	ASTM D5185(m)	>21	0		
Titanium	ppm	ASTM D5185(m)	>21	0		
Silver	ppm	ASTM D5185(m)	>21	0		
Aluminum	ppm	ASTM D5185(m)	>21	0		
Lead	ppm	ASTM D5185(m)	>21	0		
Copper	ppm	ASTM D5185(m)	>21	2		
Tin	ppm	ASTM D5185(m)	>21	0		
Antimony	ppm	ASTM D5185(m)	>21	0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		0		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		<1		
Calcium	ppm	ASTM D5185(m)		<1		
Phosphorus	ppm	ASTM D5185(m)	230	216		
Zinc	ppm	ASTM D5185(m)		2		
Sulfur	ppm	ASTM D5185(m)	5.0	25		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>25	<1		
Sodium	ppm	ASTM D5185(m)	>21	<1		
Potassium	ppm	ASTM D5185(m)	>20	0		
Water	%	ASTM D6304*	>0.0601	0.00		
ppm Water	ppm	ASTM D6304*	>601	0		







# **OIL ANALYSIS REPORT**







FLUID CLEANLIN		method	limit/base	current	history1	history2
	IESS					
Particles >4µm		ASTM D7647	>5000	96		
Particles >6µm		ASTM D7647	>640	21		
Particles >14µm		ASTM D7647	>160	3		
Particles >21µm		ASTM D7647		1		
Particles >38µm		ASTM D7647	>10	0		
Particles >71µm		ASTM D7647		0		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	14/12/9		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.90	0.89		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.0601	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	37.12	36.5		
Visc @ 100°C	cSt	ASTM D7279(m)	5.89	5.8		
Viscosity Index (VI)	Scale	ASTM D2270*	98	98		
SAMPLE IMAGES	6	method	limit/base	current	history1	history2
Color					no image	no image
				E-3		
Bottom					no image	no image



Report Id: CHECOB [WCAMIS] 02641696 (Generated: 06/14/2024 12:27:57) Rev: 1

Contact/Location: Tatiana Sorkina - CHECOB