


## **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# **EPIROC SIMBA 57 LH016**

Front Left Planetary

Fluid

SAE 80W140 (--- GAL)

#### DIAGNOSIS

#### Recommendation

The oil change at the time of sampling has been noted. Confirm the source of the lubricant being utilized for top-up/fill. Resample at the next service interval to monitor.

#### Wear

Metal levels are typical for a new component breaking in.

### Contamination

There is no indication of any contamination in the oil


### **Fluid Condition**

Viscosity of sample indicates oil is within SAE 30 range, advise investigate. This plus the additive levels indicates that this is not the same brand, or type of oil as reported. The condition of the oil is acceptable for the time in service.

				Jun 2024	,	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0937685		
Sample Date		Client Info		10 Jun 2024		
Machine Age	hrs	Client Info		359		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184*		291		
Iron	ppm	ASTM D5185(m)	>500	591		
Chromium	ppm	ASTM D5185(m)	>10	7		
Nickel	ppm	ASTM D5185(m)	>10	0		
Titanium	ppm	ASTM D5185(m)		<1		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>25	<1		
Lead	ppm	ASTM D5185(m)	>25	0		
Copper	ppm	ASTM D5185(m)	>75	3		
Tin	ppm	ASTM D5185(m)	>10	0		
Antimony	ppm	ASTM D5185(m)	>5	0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		114		
Barium	ppm	ASTM D5185(m)		22		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		8		
Magnesium	ppm	ASTM D5185(m)		6		
Calcium	ppm	ASTM D5185(m)		794		
Phosphorus	ppm	ASTM D5185(m)		725		
Zinc	ppm	ASTM D5185(m)		1528		
Sulfur	ppm	ASTM D5185(m)		6184		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	\$	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>75	153		
Sodium	ppm	ASTM D5185(m)		6		
Potassium	ppm	ASTM D5185(m)	>20	<1		



## **OIL ANALYSIS REPORT**





CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No.

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 : WC0937685

Lab Number : 02641793 Unique Number : 5799332

Received **Tested** Diagnosed Test Package : MOB 1 ( Additional Tests: PQ )

: 13 Jun 2024 : 13 Jun 2024 : 14 Jun 2024 - Kevin Marson

Agnico Eagle Canada 1350 Government Rd. W, MACASSA COMPLEX Kirkland Lake, ON

CA P2N 3J1 Contact: Mitch Lamontagne

AEM\_KL\_macassaoilsampleresults@agnicoeagle.com

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

T: (705)567-5208 F: (705)567-5221