




# OIL ANALYSIS REPORT



Machine Id  
**CATERPILLAR R1300 SCP221**  
 Component  
**Rear Right Planetary**  
 Fluid  
**PETRO CANADA PRODURO TO-4 SAE 50 (--- GAL)**

### Sample Rating Trend



**NORMAL**



### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The condition of the oil is acceptable for the time in service.

### SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>WC0949839</b>	WC0937712	WC
Sample Date	Client Info		<b>10 Jun 2024</b>	09 May 2024	01 Feb 2024
Machine Age	hrs	Client Info	<b>3866</b>	3516	0
Oil Age	hrs	Client Info	<b>0</b>	0	0
Oil Changed	Client Info		<b>Not Chngd</b>	Not Chngd	N/A
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

### CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG

### WEAR METALS

	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185(m)	>500	<b>36</b>	32	28
Chromium	ppm	ASTM D5185(m)	>10	<b>&lt;1</b>	0	<1
Nickel	ppm	ASTM D5185(m)	>10	<b>0</b>	0	0
Titanium	ppm	ASTM D5185(m)		<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185(m)		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185(m)	>25	<b>2</b>	1	2
Lead	ppm	ASTM D5185(m)	>25	<b>0</b>	0	0
Copper	ppm	ASTM D5185(m)	>75	<b>&lt;1</b>	<1	2
Tin	ppm	ASTM D5185(m)	>10	<b>0</b>	0	<1
Antimony	ppm	ASTM D5185(m)	>5	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Beryllium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Cadmium	ppm	ASTM D5185(m)		<b>0</b>	0	0

### ADDITIVES


	method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185(m)	2	<b>1</b>	2	2
Barium	ppm	ASTM D5185(m)	0	<b>&lt;1</b>	<1	0
Molybdenum	ppm	ASTM D5185(m)	0	<b>&lt;1</b>	<1	<1
Manganese	ppm	ASTM D5185(m)	0	<b>&lt;1</b>	<1	0
Magnesium	ppm	ASTM D5185(m)	9	<b>13</b>	14	13
Calcium	ppm	ASTM D5185(m)	3114	<b>3490</b>	3541	3507
Phosphorus	ppm	ASTM D5185(m)	1099	<b>888</b>	889	895
Zinc	ppm	ASTM D5185(m)	1245	<b>1058</b>	1059	1026
Sulfur	ppm	ASTM D5185(m)	7086	<b>11021</b>	10934	10433
Lithium	ppm	ASTM D5185(m)		<b>&lt;1</b>	<1	<1

### CONTAMINANTS

	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185(m)	>75	<b>14</b>	16	10
Sodium	ppm	ASTM D5185(m)		<b>2</b>	<1	<1
Potassium	ppm	ASTM D5185(m)	>20	<b>1</b>	<1	1




# OIL ANALYSIS REPORT




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	VLITE
Silt	scalar	Visual*	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	VLITE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	213.9	200	201

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : WC0949839  
**Lab Number** : **02641801**  
**Unique Number** : 5799340  
**Test Package** : MOB 1

**Agnico Eagle Canada**  
 1350 Government Rd. W, MACASSA COMPLEX  
 Kirkland Lake, ON  
 CA P2N 3J1

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.

Contact: Mitch Lamontagne  
 AEM\_KL\_macassaoilsampleresults@agnicoeagle.com  
 T: (705)567-5208  
 F: (705)567-5221