

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

[GH-9141A] 170831 HA **Unknown Component** Fluic {not provided} (--- GAL)

DIAGNOSIS

Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample. Please provide more complete information on your next sample.

Wear

All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.


Fluid Condition


Viscosity of sample indicates oil is within ISO 32 range, advise investigate. The AN level is acceptable for this fluid. The condition of the sample is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PP	PP	
Sample Date		Client Info		13 Jun 2024	07 Mar 2023	
Machine Age	hrs	Client Info		0	0	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		N/A	N/A	
Sample Status				NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method		NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184*		0	0	
Iron	ppm	ASTM D5185(m)		6	3	
Chromium	ppm	ASTM D5185(m)		0	0	
Nickel	ppm	ASTM D5185(m)		0	<1	
Titanium	ppm	ASTM D5185(m)		0	0	
Silver	ppm	ASTM D5185(m)		0	0	
Aluminum	ppm	ASTM D5185(m)		0	0	
Lead	ppm	ASTM D5185(m)		<1	<1	
Copper	ppm	ASTM D5185(m)		7	7	
Tin	ppm	ASTM D5185(m)		0	<1	
Antimony	ppm	ASTM D5185(m)		0	0	
Vanadium	ppm	ASTM D5185(m)		0	0	
Beryllium	ppm	ASTM D5185(m)		0	0	
Cadmium	ppm	ASTM D5185(m)		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<1	<1	
Barium	ppm	ASTM D5185(m)		0	0	
Molybdenum	ppm	ASTM D5185(m)		0	0	
Manganese	ppm	ASTM D5185(m)		0	<1	
Magnesium	ppm	ASTM D5185(m)		6	6	
Calcium	ppm	ASTM D5185(m)		41	42	
Phosphorus	ppm	ASTM D5185(m)		226	242	
Zinc	ppm	ASTM D5185(m)		253	247	
Sulfur	ppm	ASTM D5185(m)		2480	2635	
Lithium	ppm	ASTM D5185(m)		<1	<1	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		<1	2	
Sodium	ppm	ASTM D5185(m)		<1	<1	
Potassium	ppm	ASTM D5185(m)	>20	<1	<1	



OIL ANALYSIS REPORT






Mar7/23

	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	194	1077	
Particles >6µm		ASTM D7647	>1300	54	242	
Particles >14µm		ASTM D7647	>160	7	19	
Particles >21µm		ASTM D7647	>40	2	8	
Particles >38µm		ASTM D7647	>10	1	1	
Particles >71µm		ASTM D7647	>3	1	0	
Oil Cleanliness		ISO 4406 (c)	>19/17/14	15/13/10	17/15/11	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.30	0.31	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE	
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	
Precipitate	scalar	Visual*	NONE	NONE	NONE	
Silt	scalar	Visual*	NONE	NONE	NONE	
Debris	scalar	Visual*	NONE	NONE	NONE	
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	
Appearance	scalar	Visual*	NORML	NORML	NORML	
Odor	scalar	Visual*	NORML	NORML	NORML	
Emulsified Water	scalar	Visual*		NEG	NEG	
Free Water	scalar	Visual*		NEG	NEG	
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)		33.6	34.4	
SAMPLE IMAGES	\$	method	limit/base	current	history1	history2
Color						no image
Bottom						no image



Jun13/24



Report Id: HIBSTJ [WCAMIS] 02641962 (Generated: 06/18/2024 13:08:22) Rev: 1

Contact/Location: Michelle Jefford - HIBSTJ Page 2 of 2