

# **OIL ANALYSIS REPORT**

[13998089] 170831 EB

Unknown Component

**AW HYDRAULIC OIL ISO 32 (--- GAL)** 

# Sample Rating Trend



# DIAGNOSIS

## Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample. Please provide more complete information on your next sample.

### Wear

All component wear rates are normal.

### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.


### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the sample is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		wc	PP	
Sample Date		Client Info		13 Jun 2024	18 Apr 2024	
Machine Age	hrs	Client Info		0	0	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		N/A	N/A	
Sample Status				NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method		NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184*		0	0	
Iron	ppm	ASTM D5185(m)		6	6	
Chromium	ppm	ASTM D5185(m)		0	0	
Nickel	ppm	ASTM D5185(m)		0	0	
Titanium	ppm	ASTM D5185(m)		0	0	
Silver	ppm	ASTM D5185(m)		0	0	
Aluminum	ppm	ASTM D5185(m)		0	0	
Lead	ppm	ASTM D5185(m)		<1	<1	
Copper	ppm	ASTM D5185(m)		7	7	
Tin	ppm	ASTM D5185(m)		0	0	
Antimony	ppm	ASTM D5185(m)		0	0	
Vanadium	ppm	ASTM D5185(m)		0	0	
Beryllium	ppm	ASTM D5185(m)		0	0	
Cadmium	ppm	ASTM D5185(m)		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	5	<1	<1	
Barium	ppm	ASTM D5185(m)	5	0	0	
Molybdenum	ppm	ASTM D5185(m)	5	0	0	
Manganese	ppm	ASTM D5185(m)		0	0	
Magnesium	ppm	ASTM D5185(m)	25	6	6	
Calcium	ppm	ASTM D5185(m)	200	42	42	
Phosphorus	ppm	ASTM D5185(m)	300	223	220	
Zinc	ppm	ASTM D5185(m)	370	255	250	
Sulfur	ppm	ASTM D5185(m)	2500	2515	2563	
Lithium	ppm	ASTM D5185(m)		<1	<1	
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		<1	<1	
Sodium	ppm	ASTM D5185(m)		<1	0	
Potassium	ppm	ASTM D5185(m)	>20	<1	<1	



# **OIL ANALYSIS REPORT**



FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	217	266	
Particles >6µm		ASTM D7647	>1300	49	67	
Particles >14µm		ASTM D7647	>160	4	4	
Particles >21µm		ASTM D7647	>40	1	2	
Particles >38µm		ASTM D7647	>10	0	1	
Particles >71µm		ASTM D7647	>3	0	1	
Oil Cleanliness		ISO 4406 (c)	>19/17/14	15/13/9	15/13/9	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.57	0.19	0.29	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE	
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	
Precipitate	scalar	Visual*	NONE	NONE	NONE	
Silt	scalar	Visual*	NONE	NONE	NONE	
Debris	scalar	Visual*	NONE	NONE	NONE	
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	
Appearance	scalar	Visual*	NORML	NORML	NORML	
Odor	scalar	Visual*	NORML	NORML	NORML	
<b>Emulsified Water</b>	scalar	Visual*		NEG	NEG	
Free Water	scalar	Visual*		NEG	NEG	
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	32	33.5	33.6	
SAMPLE IMAGES	;	method	limit/base	current	history1	history2
Color				AID		no image
Bottom						no image





Laboratory Sample No.

Lab Number : 02641990 Unique Number : 5799529

: WC

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9

Received **Tested** 

Diagnosed Test Package : IND 2 (Additional Tests: PQ, PRTCOUNT)

: 18 Jun 2024 : 18 Jun 2024 - Kevin Marson

: 14 Jun 2024

HIBERNIA MGMT & DEVELOPMENT CO. LTD SUITE 1000,, 100 NEW GOWER STREET ST.JOHNS, NL CA A1C 6K3

Contact: Sam Nash samantha.m.nash@exxonmobil.com T:

F: (709)722-3766

Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

To discuss this sample report, contact Customer Service at 1-800-268-2131.

Contact/Location: Sam Nash - HIBSTJ