

## **OIL ANALYSIS REPORT**

Sample Rating Trend

### NORMAL

## Area EAST CRANE [M9131B] 170832 AGG #2

**1 Distribution Gear** Fluic GEAR OIL LS 80W90 (--- GAL)

#### DIAGNOSIS

#### Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition


The oil viscosity is higher than typical. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


		Sep2022	Nov2022	Mar2023 Apr2024	Jun2024	
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC	PP	PP
Sample Date		Client Info		13 Jun 2024	18 Apr 2024	07 Mar 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184*	>200	0	0	0
Iron	ppm	ASTM D5185(m)	>185	14	15	20
Chromium	ppm	ASTM D5185(m)	>5	0	0	0
Nickel	ppm	ASTM D5185(m)	>10	0	0	0
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)		0	0	0
Aluminum	ppm	ASTM D5185(m)	>10	0	<1	<1
Lead	ppm	ASTM D5185(m)	>35	0	0	0
Copper	ppm	ASTM D5185(m)	>35	13	13	12
Tin	ppm	ASTM D5185(m)	>5	0	0	0
Antimony	ppm	ASTM D5185(m)	>5	0	0	<1
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	0
ADDITIVES		method	limit/base	current	history1	history2

						J
Boron	ppm	ASTM D5185(m)	150	3	<1	1
Barium	ppm	ASTM D5185(m)		<1	<1	<1
Molybdenum	ppm	ASTM D5185(m)		0	0	0
Manganese	ppm	ASTM D5185(m)		<1	<1	2
Magnesium	ppm	ASTM D5185(m)	10	<1	<1	1
Calcium	ppm	ASTM D5185(m)	70	5	5	15
Phosphorus	ppm	ASTM D5185(m)	2000	452	461	673
Zinc	ppm	ASTM D5185(m)	50	85	78	98
Sulfur	ppm	ASTM D5185(m)	20000	5134	4902	10033
Lithium	ppm	ASTM D5185(m)		<1	<1	<1
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>150	9	8	6
Sodium	ppm	ASTM D5185(m)		2	<1	2
Potassium	ppm	ASTM D5185(m)	>20	1	<1	1
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.79	0.69	0.94





# **OIL ANALYSIS REPORT**





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	NONE	VLITE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	140	186	190	176
SAMPLE IMAGES	\$	method	limit/base	current	history1	history2
Color					21P	
Bottom						





Report Id: HIBSTJ [WCAMIS] 02642132 (Generated: 06/18/2024 17:10:26) Rev: 1

Contact/Location: Sam Nash - HIBSTJ Page 2 of 2