

## **OIL ANALYSIS REPORT**

Sample Rating Trend



### Area General Recycling - 888097 A2406108

Hydraulic System Fluid {not provided} (--- GAL)

#### DIAGNOSIS


#### Recommendation


We certify that this oil is clean, that the additives are at acceptable levels, and that it is suitable for use.


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Machine ID		Client Info		Tote 2 - Bottom		
Department		Client Info		Sales		
Sample From		Client Info		Machine		
Production Stage		Client Info		Lab Reclaim		
Sent to WC		Client Info		06/17/2024		
Sample Number		Client Info		E30002406		
Sample Date		Client Info		17 Jun 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	1		
Chromium	ppm	ASTM D5185(m)	>20	0		
Nickel	ppm	ASTM D5185(m)	>20	<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		<1		
Aluminum	ppm	ASTM D5185(m)	>20	<1		
Lead	ppm	ASTM D5185(m)	>20	0		
Copper	ppm	ASTM D5185(m)	>20	3		
Tin	ppm	ASTM D5185(m)	>20	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<1		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		6		
Calcium	ppm	ASTM D5185(m)		53		
Phosphorus	ppm	ASTM D5185(m)		341		
Zinc	ppm	ASTM D5185(m)		416		
Sulfur	ppm	ASTM D5185(m)		1170		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	2		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	<1		
Water	%	ASTM D6304*	>0.05	0.00		
ppm Water	ppm	ASTM D6304*	>500	0		




# **OIL ANALYSIS REPORT**










FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	186		
Particles >6µm		ASTM D7647	>640	73		
Particles >14µm		ASTM D7647	>160	10		
Particles >21µm		ASTM D7647	>40	3		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	1		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	15/13/10		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.41		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.05	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)		27.9		
Visc @ 100°C	cSt	ASTM D7279(m)		5.1		
Viscosity Index (VI)	Scale	ASTM D2270*		111		
SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Color					no image	no image





Report Id: CHECOB [WCAMIS] 02642937 (Generated: 06/21/2024 08:18:37) Rev: 1

Contact/Location: Tatiana Sorkina - CHECOB Page 2 of 2

no image

no image