

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id **TICO 827-8987**

Component Diesel Engine Fluid DIESEL ENGINE OIL SAE 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) DIESEL ENGINE OIL SAE 15W40. Please confirm.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0683841		
Sample Date		Client Info		14 May 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION	٧	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>100	21		
Chromium	ppm	ASTM D5185(m)	>20	<1		
Nickel	ppm	ASTM D5185(m)	>4	<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)	>3	<1		
Aluminum	ppm	ASTM D5185(m)	>20	4		
Lead	ppm	ASTM D5185(m)	>40	0		
Copper	ppm	ASTM D5185(m)	>330	<1		
Tin	ppm	ASTM D5185(m)	>15	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	250	69		
Barium	ppm	ASTM D5185(m)	10	0		
Molybdenum	ppm	ASTM D5185(m)	100	14		
Manganese	ppm	ASTM D5185(m)		<1		
Magnesium	ppm	ASTM D5185(m)	450	195		
Calcium	ppm	ASTM D5185(m)	3000	1911		
Phosphorus	ppm	ASTM D5185(m)	1150	885		
Zinc	ppm	ASTM D5185(m)	1350	1128		
Sulfur	ppm	ASTM D5185(m)	4250	2629		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>25	3		
Sodium	ppm	ASTM D5185(m)	>158	2		
Potassium	ppm	ASTM D5185(m)	>20	6		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*	>3	1.2		
Nitration	Abs/cm	ASTM D7624*	>20	11.0		
Sulfation	Abs/.1mm	ASTM D7415*	>30	26.1		



4(

35

30 Weight and the second seco

140 T Abnormal

130

120 CSt (10°C) 110 100

> 90 Abnorm 80 +7/51/6W

90 80 47/41/2000

140 Abnormal 130 -120 Base 0 100 -

FT-IR (Direct Trend)

Oxidation

Nitration Sulfation

Viscosity @ 40°C

Viscosity @ 40°C

OIL ANALYSIS REPORT

	FLUID DEGRADA	method	limit/base	current	history1	history2	
	Oxidation	Abs/.1mm	ASTM D7414*	>25	20.4		
	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	Visual*	NONE	NONE		
	Yellow Metal	scalar	Visual*	NONE	NONE		
	Precipitate	scalar	Visual*	NONE	NONE		
4/24 -	Silt	scalar	Visual*	NONE	NONE		
May14/24	Debris	scalar	Visual*	NONE	NONE		
	Sand/Dirt	scalar	Visual*	NONE	NONE		
	Appearance	scalar	Visual*	NORML	NORML		
	Odor	scalar	Visual*	NORML	NORML		
	Emulsified Water	scalar	Visual*	>0.2	NEG		
	Free Water	scalar	Visual*		NEG		
	FLUID PROPERT	IES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D7279(m)	115	114		
4/24 -	Visc @ 100°C	cSt	ASTM D7279(m)	14.4	14.9		
May14/24	Viscosity Index (VI)	Scale	ASTM D2270*	126	135		
	GRAPHS						
	Iron (ppm)			10	Lead (ppm)		
	Sminn			10	Severe		
	E .			E 5	Abnormal		
	abnormal			-	0		
	0			4			
	May14/24			May14/24	ay14/24		AC A Loo M
2 2	≊ Aluminum (ppm)			W	≊ Chromium (pj)	W.
ан. - уу			6				
	40 Severe		4	Severe			
	Abnormal			Ed 2	Abnormal		
	0						
				4/24	4/24		6.04
	May14/24			May14/24	May1		10 PP-M
	Copper (ppm)				Silicon (ppm)		
	400 Severe				Severe		
	300 - E 200 -			61 Ed.41			
	100			범· 1	Abnormal		
	0				, L		
	May14/24			May14/24	May14/24		ACAL
				Mar			N
	Viscosity @ 100°C			6.	Soot %		
	Abnormal				Severe		
	G 16 Base 14 K 12 Abnormal			_{هو} 4. تو 2.	Abnormal		
	3 12 - Abnormal						
	10				and a		
	May14/24			May14/24	May14/24		10 provem
	W			M	N		2 2
CALA Laboratory	: WearCheck - C8-1175	5 Appleb	/ Line, Burlin	gton, ON L7	L 5H9 B	RITANNIA FLE	ET SERVICE
		Recei) Jun 2024		31 SHAWSON I	
Sample No.							(
o 17025:2017 Lab Numbe		Teste Diagr		Jun 2024 Jun 2024 - W			ISSAUGA, OI CA L4W 1T

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

Report Id: BRI183MIS [WCAMIS] 02643115 (Generated: 06/21/2024 10:32:01) Rev: 1

Contact/Location: Tania Henriques - BRI183MIS

T: (905)670-4545

F: (905)670-9036