

OIL ANALYSIS REPORT

Sample Rating Trend





CATERPILLAR 980H 2230704

Component Front Right Planetary

{not provided} (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0914638		
Sample Date		Client Info		25 Jun 2024		
Machine Age	hrs	Client Info		27735		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>500	15		
Chromium	ppm	ASTM D5185(m)	>10	0		
Nickel	ppm	ASTM D5185(m)	>10	<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>25	1		
Lead	ppm	ASTM D5185(m)	>25	0		
Copper	ppm	ASTM D5185(m)	>75	2		
Tin	ppm	ASTM D5185(m)	>10	0		
Antimony	ppm	ASTM D5185(m)	>5	0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		91		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		6		
Manganese	ppm	ASTM D5185(m)		<1		
Magnesium	ppm	ASTM D5185(m)		47		
Calcium	ppm	ASTM D5185(m)		3372		
Phosphorus	ppm	ASTM D5185(m)		1081		
Zinc	ppm	ASTM D5185(m)		1345		
Sulfur	ppm	ASTM D5185(m)		6329		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	1	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>75	10		
Sodium	ppm	ASTM D5185(m)		<1		
Potassium	ppm	ASTM D5185(m)	>20	<1		



OIL ANALYSIS REPORT

VICUAL



VISUAL		method	limit/base	current	history1	history
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	VLITE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.2	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history
Visc @ 40°C	cSt	ASTM D7279(m)		60.7		
SAMPLE IMAGES	5	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image
GRAPHS	· · · ·					
Iron (ppm)			150	Lead (ppm)		
Severe				Smillion		
Abnormal			E 100	Abnormal		
24 0			24) 🖵		
Jun 25/24			Jun25/24	Jun25/24		
Aluminum (ppm)			7	S Chromium (pp	m)	
100 Severe			3	T Severe	,	
50			e ²⁰	Abnormal		
Abnormal			⁻ 10			
5/24			5/24 -	5/24		
Jun25,24			Jun25/24	Jun25/24		
Copper (ppm)				Silicon (ppm)		
200 Severe			300	Severe		
100 - Abnormal			튼 ²⁰⁰			
0) L <u>i</u>		
Jun25/24			Jun25/24	Jun25/24		
			Jur			
Viscosity @ 40°C			4000	Additives		
			200	calcium		
5 150 - Abnormal 5 100 - Abnormal			E 2000) - zinc		
50			1000			
Jun25/24			Jun25/24	Jun25/24		
: WearCheck - C8-1175 : WC0914638 : 02644649 : 5802188	Recei Teste	ived : 28 ed : 28		L 5H9	E.C. KING C 2125 - 20TH <i>J</i> OWE	

 To discuss this sample report, contact Customer Service at 1-800-268-2131.

 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

 Validity of results and interpretation are based on the sample and information as supplied.

Report Id: ECKOWE [WCAMIS] 02644649 (Generated: 06/28/2024 14:34:40) Rev: 1

CALA

ISO 17025:2017 Accredited Laboratory

Contact/Location: Daniel Fleet - ECKOWE Page 2 of 2

F: (519)371-2783