

OIL ANALYSIS REPORT

Area AIM Recycling Windsor - 888101 RB042

Hydraulic System Fluid PETRO CANADA HYDREX AW 46 (--- GAL)

DIAGNOSIS


Recommendation

The sample submitted is 2 times dirtier than the ISO dirt count recommendation of 19/16/14.

Contamination


Particles >4 μ m are notably high. Particles >6 μ m and oil cleanliness are notably high.


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Machine ID		Client Info		Press #2		
Department		Client Info		Sales		
Sample From		Client Info		Machine		
Production Stage		Client Info		Initial		
Sent to WC		Client Info		06/28/2024		
Sample Number		Client Info		E30002528		
Sample Date		Client Info		25 Jun 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ATTENTION		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	1		
Chromium	ppm	ASTM D5185(m)	>20	0		
Nickel	ppm	ASTM D5185(m)	>20	<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)		<1		
Lead	ppm	ASTM D5185(m)	>20	0		
Copper	ppm	ASTM D5185(m)		<1		
Tin	ppm	ASTM D5185(m)	>20	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	0	1		
Barium	ppm	ASTM D5185(m)	0	0		
Molybdenum	ppm	ASTM D5185(m)	0	0		
Manganese	ppm	()	0	0		
Magnesium	ppm	ASTM D5185(m)	0	4		
Calcium	ppm	ASTM D5185(m)	50	74		
Phosphorus	ppm	ASTM D5185(m)	330	330		
Zinc	ppm	ASTM D5185(m)	430	430		
Sulfur	ppm	ASTM D5185(m)	760	739		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	0		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	<1		
Water	%	ASTM D6304*	>0.05	0.005		
ppm Water	ppm	ASTM D6304*	>500	57		






OIL ANALYSIS REPORT








FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	6890		
Particles >6µm		ASTM D7647	>640	986		
Particles >14µm		ASTM D7647	>160	53		
Particles >21µm		ASTM D7647	>40	11		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	e 20/17/13		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.70	0.40		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	VLITE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	WGOIL		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.05	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	46.4	45.6		
Visc @ 100°C	cSt	ASTM D7279(m)	6.92	7.2		
Viscosity Index (VI)	Scale	ASTM D2270*	104	118		
SAMPLE IMAGES	3	method	limit/base	current	history1	history2
				and		
Color					no image	no image

Bottom



Report Id: CHECOB [WCAMIS] 02645459 (Generated: 07/08/2024 08:42:25) Rev: 1

Contact/Location: Tatiana Sorkina - CHECOB

no image

no image