

# **OIL ANALYSIS REPORT**

### **VISUAL METAL**

### 



history2

WC0864636

0

0

N/A

NORMAL

history2

#### SAMPLE INFORMATION method limit/base current history1 WC0933968 Sample Number Client Info WC0864646 Sample Date Client Info 03 Jul 2024 15 May 2024 21 Dec 2023 0 Machine Age hrs **Client Info** 0 Oil Age hrs Client Info 0 0 Oil Changed **Client Info** N/A N/A MARGINAL NORMAL Sample Status CONTAMINATION method limit/base current history1

Water		WC Method	>2	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>85	2	2	2
Chromium	ppm	ASTM D5185(m)	>20	0	0	0
Nickel	ppm	ASTM D5185(m)	>20	<1	<1	<1
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)		0	0	0
Aluminum	ppm	ASTM D5185(m)	>40	<1	0	<1
Lead	ppm	ASTM D5185(m)	>60	0	0	<1
Copper	ppm	ASTM D5185(m)	>7	<1	<1	<1
Tin	ppm	ASTM D5185(m)	>40	0	0	0
Antimony	ppm	ASTM D5185(m)		0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	0	<1	<1	0
Barium	ppm	ASTM D5185(m)		0	0	0
Molybdenum	ppm	ASTM D5185(m)	0	0	0	0
Manganese	ppm	ASTM D5185(m)		0	0	0
Magnesium	ppm	ASTM D5185(m)	0	0	0	0
Calcium	ppm	ASTM D5185(m)	0	<1	0	<1
Phosphorus	ppm	ASTM D5185(m)	2.4	2	2	<1
Zinc	ppm	ASTM D5185(m)	0	2	2	2
Sulfur	ppm	ASTM D5185(m)		1181	1270	1378
Lithium	ppm	ASTM D5185(m)		<1	<1	<1
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>20	<1	<1	1
Sodium	ppm	ASTM D5185(m)		0	0	0

Potassium	ppm	ASTM D5185(m)	>20	<1	<1	1
FLUID CLEANLI	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	2633	611	79
Particles >6µm		ASTM D7647	>1300	724	153	26
Particles >14µm		ASTM D7647	>160	88	8	4
Particles >21µm		ASTM D7647	>40	23	2	2
Particles >38µm		ASTM D7647	>10	2	1	0
Particles >71µm		ASTM D7647	>3	0	1	0
Oil Cleanliness		ISO 4406 (c)	>20/17/14	19/17/14	16/14/10	13/12/9

## SAB1 G4 **Thrust Bearing** ESSO TERESSO ISO 46 (1182 LTR)

#### DIAGNOSIS

Area SAB1

#### Recommendation

We advise that you check for visible metal particles in the oil. We recommend an early resample to monitor this condition. Please contact your representative for information regarding the proper sampling kits for your service. NOTE: We recommend using IND 3 test kits, this testkit includes Analytical Ferrography which provides a detailed morphological analysis of wear particles present in the fluid.

#### A Wear


Light concentration of visible metal present. All other component wear rates are normal.

#### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.






Report Id: ONTQUE [WCAMIS] 02645511 (Generated: 07/09/2024 16:58:18) Rev: 1




Darticla Count

# **OIL ANALYSIS REPORT**

380 Severe					-24
Abnom	nal 🖕				-22
680					-20
920		144			-18
180-					-16
120-		-			-14
30-					+20 +18 +16 +14 +12 +10
8-					-10
2-					-8
					Contraction of the local division of the loc
	<sup>6µ</sup> I Numbe	14µ er	21µ	38 <sup>j</sup> µ	71µ
Acio	l Numbe		21µ	38µ	71µ
Acio	l Numbe		21µ	38µ	71µ
Acio	l Numbe		21µ	38µ	71µ
Acio	l Numbe		21µ	38µ	71µ





FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.02	0.12	0.11	0.17
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE		NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>2	NEG	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	46	46.2	46.4	46.1
SAMPLE IMAGES		method	limit/base	current	history1	history2

Color

Bottom

PrtFilter



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **Ontario Power Generation** CALA Sample No. : WC0933968 Received : 04 Jul 2024 NIAGARA PLANT GROUP,, 14000 NIAGARA PKWY Lab Number : 02645511 Tested : 09 Jul 2024 NIAGARA ON THE LAKE, ON ISO 17025:2017 Accredited Laboratory Unique Number : 5803050 Diagnosed : 09 Jul 2024 - Kevin Marson CA LOS 1J0 Test Package : IND 2 (Additional Tests: BottomAnalysis, FilterPatch, PrtFilter, TAN Man) Contact: Michael Brochu mike.brochu@opg.com To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab. T: (905)357-0322 F: (905)374-5466 Validity of results and interpretation are based on the sample and information as supplied.

Report Id: ONTQUE [WCAMIS] 02645511 (Generated: 07/09/2024 16:58:19) Rev: 1

Submitted By: ? Page 2 of 2