




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id

2267

Component

Natural Gas Engine

Fluid

VALVOLINE PREMIUM BLUE 9200 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			WC0937116	WC0937091	---
Sample Date	Client Info			02 Jul 2024	06 May 2024	---
Machine Age	kms	Client Info		9272	1621	---
Oil Age	kms	Client Info		0	0	---
Oil Changed	Client Info			N/A	N/A	---
Sample Status				NORMAL	NORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Water	WC Method		>0.1	NEG	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>50	17	28	---
Chromium	ppm	ASTM D5185(m)	>4	<1	0	---
Nickel	ppm	ASTM D5185(m)	>2	<1	<1	---
Titanium	ppm	ASTM D5185(m)		0	0	---
Silver	ppm	ASTM D5185(m)	>3	0	0	---
Aluminum	ppm	ASTM D5185(m)	>9	1	1	---
Lead	ppm	ASTM D5185(m)	>30	0	0	---
Copper	ppm	ASTM D5185(m)	>35	3	14	---
Tin	ppm	ASTM D5185(m)	>4	<1	0	---
Antimony	ppm	ASTM D5185(m)		0	0	---
Vanadium	ppm	ASTM D5185(m)		0	0	---
Beryllium	ppm	ASTM D5185(m)		0	0	---
Cadmium	ppm	ASTM D5185(m)		0	0	---

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		15	34	---
Barium	ppm	ASTM D5185(m)		<1	3	---
Molybdenum	ppm	ASTM D5185(m)		53	49	---
Manganese	ppm	ASTM D5185(m)		2	13	---
Magnesium	ppm	ASTM D5185(m)		793	763	---
Calcium	ppm	ASTM D5185(m)		1217	1162	---
Phosphorus	ppm	ASTM D5185(m)		681	724	---
Zinc	ppm	ASTM D5185(m)		833	812	---
Sulfur	ppm	ASTM D5185(m)		1901	1971	---
Lithium	ppm	ASTM D5185(m)		<1	<1	---



CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>+100	14	38	---
Sodium	ppm	ASTM D5185(m)		3	5	---
Potassium	ppm	ASTM D5185(m)	>20	<1	2	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*		0	0	---
Nitration	Abs/cm	ASTM D7624*	>20	11.9	7.8	---
Sulfation	Abs/.1mm	ASTM D7415*	>30	20.9	20.3	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	ASTM D7414*	>25	19.1	17.2	---











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	14.8	14.3	13.6

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : WC0937116 **Received** : 05 Jul 2024
Lab Number : 02645753 **Tested** : 05 Jul 2024
Unique Number : 5803292 **Diagnosed** : 05 Jul 2024 - Wes Davis
Test Package : MOB 1

CITY OF HAMILTON
 2200 UPPER JAMES., MOUNTAIN TRANSIT STOREROOM
 MOUNT HOPE, ON
 CA L0R 1W0
 Contact: Jeff Parr
 jeff.parr@hamilton.ca
 T: (905)546-2424
 F: (905)679-4502

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.