


OIL ANALYSIS REPORT

UNASSIGNED ICON 3 (S/N 98271)

Hydraulic System

DOW CHEMICAL UCON TRIDENT AW 46 (600 GAL)





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please contact your representative for information regarding the proper sampling kits for your service. NOTE: We recommend using IND 3 test kits, this testkit includes Analytical Ferrography which provides a detailed morphological analysis of wear particles present in the fluid.

Component wear rates appear to be normal (unconfirmed).

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION method limit/base current history1 history2 Sample Number Client Info O4 Jul 2024 06 Jun 2024 Machine Age days Client Info O8 1	(600 GAL)			Jun2024	Jul2024		
Sample Date Client Info 04 Jul 2024 06 Jun 2024	SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Date Client Info 04 Jul 2024 06 Jun 2024	Sample Number		Client Info		WC0956235	WC0787419	
Machine Age days Client Info 8 1 Oil Age days Client Info 8 1 Oil Changed Client Info Not Changed Filtered Sample Status Image: Control of Morith Info North Machine Image: Control of Morith Info North Machine CONTAMINATION method Imitibass current history1 history2 WEAR METALS method Imitibass current history1 history2 Iron ppm ASTM D5185(m) >20 0 0 Nickel ppm ASTM D5185(m) >20 0 0 Niker ppm ASTM D5185(m) >20 0 0 Aluminum ppm ASTM D5185(m) >20 0 0 Lead ppm ASTM D5185(m) >20 0 0 Aprice ppm ASTM D5185(m) >20 0 0	·						
Oil Age days Client Info Not Changd NorMAL Filtered Sample Status Client Info NoRMAL NORMAL CONTAMINATION method limit/base current history1 history2 Water WC Method >0.05 NEG NEG WEAR METALS method limit/base current history1 history2 Iron ppm ASTM05185(m) >20 0 0 Chromium ppm ASTM05185(m) >20 0 0 Nickel ppm ASTM05185(m) >20 0 0 Sliver ppm ASTM05185(m) >20 0 0 Lead ppm ASTM05185(m) >20 0 0 Copper ppm ASTM05185(m) >20 0 0 Vanadium ppm ASTM05185(m) 0 0 <td></td> <td>days</td> <td></td> <td></td> <td></td> <td></td> <td></td>		days					
Oil Changed Sample Status					_		
Sample Status	•	aayo			•		
Water WC Method >0.05 NEG NEG WEAR METALS method limit/base current history1 history2 Iron ppm ASTM D5185(m) >20 0 0 Chromium ppm ASTM D5185(m) >20 0 0 Nickel ppm ASTM D5185(m) >20 0 0 Silver ppm ASTM D5185(m) >20 0 0 Aluminum ppm ASTM D5185(m) >20 0 0 Aluminum ppm ASTM D5185(m) >20 0 0 Aluminum ppm ASTM D5185(m) >20 0 0 Tin ppm ASTM D5185(m) >20 0 0 Antimony ppm ASTM D5185(m) 0 0 Vanadium ppm ASTM D5185(m) 0 0 </th <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>							
WEAR METALS method limit/base current history1 history2 Iron ppm ASTM DS185(m) >20 0 0	CONTAMINATION	V	method	limit/base	current	history1	history2
Iron	Water		WC Method	>0.05	NEG	NEG	
Chromium ppm ASTM D5185(m) >20 0 0 Nickel ppm ASTM D5185(m) 20 0 0 Titanium ppm ASTM D5185(m) 20 0 0 Aluminum ppm ASTM D5185(m) >20 0 0 Lead ppm ASTM D5185(m) >20 0 0 Copper ppm ASTM D5185(m) >20 0 0 Antimony ppm ASTM D5185(m) >20 0 0 Nantidum ppm ASTM D5185(m) 0 0 Vanadium ppm ASTM D5185(m) 0 0 Beryllium ppm ASTM D5185(m) 0 0 Beryllium ppm ASTM D5185(m) 0 0 Beryllium ppm ASTM D5185(m) 0 0 Barium <td>WEAR METALS</td> <td></td> <td>method</td> <td>limit/base</td> <td>current</td> <td>history1</td> <td>history2</td>	WEAR METALS		method	limit/base	current	history1	history2
Nickel ppm ASTM D5185(m) >20 0 0 Titanium ppm ASTM D5185(m) 0 0 Silver ppm ASTM D5185(m) >20 0 0 Aluminum ppm ASTM D5185(m) >20 0 0 Lead ppm ASTM D5185(m) >20 0 0 Copper ppm ASTM D5185(m) >20 0 0 Tin ppm ASTM D5185(m) >20 0 0 Antimony ppm ASTM D5185(m) 0 0 0 Vanadium ppm ASTM D5185(m) 0 0 0 Vanadium ppm ASTM D5185(m) 0 0 Cadmium ppm ASTM D5185(m) 0 0 Barium ppm ASTM D5185(m) 0 0 Bar	Iron	ppm	ASTM D5185(m)	>20	0	0	
Nickel ppm ASTM D5185(m) >20 0 0 Titanium ppm ASTM D5185(m) 0 0 Silver ppm ASTM D5185(m) >20 0 0 Aluminum ppm ASTM D5185(m) >20 0 0 Lead ppm ASTM D5185(m) >20 0 0 Copper ppm ASTM D5185(m) >20 0 0 Tin ppm ASTM D5185(m) >20 0 0 Antimony ppm ASTM D5185(m) 0 0 0 Vanadium ppm ASTM D5185(m) 0 0 0 Vanadium ppm ASTM D5185(m) 0 0 Cadmium ppm ASTM D5185(m) 0 0 ADDITIVES method limit/base current history1 history2	Chromium		ASTM D5185(m)	>20	0	0	
Titanium	Nickel		ASTM D5185(m)	>20	0	0	
Aluminum ppm ASTM D5185(m) >20 0 0 0	Titanium	ppm	ASTM D5185(m)		0	0	
Aluminum	Silver		. ,		<1	0	
Lead ppm ASTM D5185(m) >20 <1 0 Copper ppm ASTM D5185(m) >20 <1	Aluminum		ASTM D5185(m)	>20	0	0	
Copper ppm ASTM D5185(m) >20 <1 0 Tin ppm ASTM D5185(m) >20 0 0 Antimony ppm ASTM D5185(m) 0 0 Vanadium ppm ASTM D5185(m) 0 0 Beryllium ppm ASTM D5185(m) 0 0 Cadmium ppm ASTM D5185(m) 0 0 ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185(m) 0 0 Molybdenum ppm ASTM D5185(m) 0 0 Molybdenum ppm ASTM D5185(m) 0 0 Magnesium ppm ASTM D5185(m) <1	Lead		(/	>20	0	0	
Tin ppm ASTM D5185(m) >20 0 0 Antimony ppm ASTM D5185(m) 0 0 Vanadium ppm ASTM D5185(m) 0 0 Beryllium ppm ASTM D5185(m) 0 0 Cadmium ppm ASTM D5185(m) 0 0 ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185(m) 0 0	Copper		ASTM D5185(m)	>20	<1	0	
Antimony ppm ASTM D5185(m) 0 0 Vanadium ppm ASTM D5185(m) 0 0 Beryllium ppm ASTM D5185(m) 0 0 Cadmium ppm ASTM D5185(m) 0 0 ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185(m) 0 0 Barium ppm ASTM D5185(m) 0 0 Molybdenum ppm ASTM D5185(m) 0 0 Magnesium ppm ASTM D5185(m) <1			1 /	>20	0	0	
Vanadium ppm ASTM D5185(m) 0 0 Beryllium ppm ASTM D5185(m) 0 0 Cadmium ppm ASTM D5185(m) 0 0 ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185(m) <1 1 Barium ppm ASTM D5185(m) 0 0 Molybdenum ppm ASTM D5185(m) 0 0 Magnesium ppm ASTM D5185(m) <1 <1 Magnesium ppm ASTM D5185(m) <1 <1 Calcium ppm ASTM D5185(m) <1 <1 Phosphorus ppm ASTM D5185(m) 428 369 Zinc ppm ASTM D5185(m) 7 5 Sulfur ppm ASTM D5185(m) 7 5	Antimony		\ /				
Beryllium	•		1 /				
Cadmium ppm ASTM D5185(m) 0 0 ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185(m) <1			. ,				
Boron ppm ASTM D5185(m) <1 1 Barium ppm ASTM D5185(m) 0 0 Molybdenum ppm ASTM D5185(m) 0 0 Manganese ppm ASTM D5185(m) 0 0 Magnesium ppm ASTM D5185(m) <1 <1 Calcium ppm ASTM D5185(m) <1 <1 Phosphorus ppm ASTM D5185(m) 428 369 Zinc ppm ASTM D5185(m) 1 2 Sulfur ppm ASTM D5185(m) 7 5 Lithium ppm ASTM D5185(m) >15 0 0 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185(m) >15 0 0 Sodium ppm ASTM D5185(m) >20	-		. ,				
Barium ppm ASTM D5185(m) 0 0 Molybdenum ppm ASTM D5185(m) 0 0 Manganese ppm ASTM D5185(m) 0 0 Magnesium ppm ASTM D5185(m) <1	ADDITIVES		method	limit/base	current	history1	history2
Barium ppm ASTM D5185(m) 0 0 Molybdenum ppm ASTM D5185(m) 0 0 Manganese ppm ASTM D5185(m) 0 0 Magnesium ppm ASTM D5185(m) <1	Boron	ppm	ASTM D5185(m)		<1	1	
Molybdenum ppm ASTM D5185(m) 0 0 Manganese ppm ASTM D5185(m) <1	Barium		ASTM D5185(m)		0	0	
Manganese ppm ASTM D5185(m) 0 0 Magnesium ppm ASTM D5185(m) <1	Molybdenum		, ,		0	0	
Magnesium ppm ASTM D5185(m) <1 <1 Calcium ppm ASTM D5185(m) <1			. ,		0		
Calcium ppm ASTM D5185(m) <1 <1 Phosphorus ppm ASTM D5185(m) 428 369 Zinc ppm ASTM D5185(m) 7 5 Sulfur ppm ASTM D5185(m) 7 5 Lithium ppm ASTM D5185(m) <1	•				<1	<1	
Phosphorus ppm ASTM D5185(m) 428 369 Zinc ppm ASTM D5185(m) 1 2 Sulfur ppm ASTM D5185(m) 7 5 Lithium ppm ASTM D5185(m) <1	-		. ,		<1	<1	
Zinc ppm ASTM D5185(m) 1 2			(/		428	369	
Sulfur ppm ASTM D5185(m) 7 5 Lithium ppm ASTM D5185(m) <1 <1 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185(m) >15 0 0 Sodium ppm ASTM D5185(m) >1 1 1 Potassium ppm ASTM D5185(m) >20 <1 <1 FLUID CLEANLINESS method limit/base current history1 history2 Particles >4μm ASTM D7647 >5000 298 1625 Particles >6μm ASTM D7647 >1300 70 788 Particles >1μm ASTM D7647 >160 8 114 Particles >21μm ASTM D7647 >40 2 31 Particles >71μm ASTM D7647 >10 4 Pa			. ,		1		
Lithium ppm ASTM D5185(m) <1 <1 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185(m) >15 0 0 Sodium ppm ASTM D5185(m) >20 <1	Sulfur					5	
Silicon ppm ASTM D5185(m) >15 0 0 Sodium ppm ASTM D5185(m) 1 1 1 Potassium ppm ASTM D5185(m) >20 <1 <1 FLUID CLEANLINESS method limit/base current history1 history2 Particles >4μm ASTM D7647 >5000 298 1625 Particles >6μm ASTM D7647 >1300 70 788 Particles >14μm ASTM D7647 >160 8 114 Particles >21μm ASTM D7647 >40 2 31 Particles >38μm ASTM D7647 >10 0 4 Particles >71μm ASTM D7647 >3 0 1	Lithium		. ,		<1	<1	
Sodium ppm ASTM D5185(m) 1 1 Potassium ppm ASTM D5185(m) >20 <1	CONTAMINANTS		method	limit/base	current	history1	history2
Sodium ppm ASTM D5185(m) 1 1 Potassium ppm ASTM D5185(m) >20 <1 <1 FLUID CLEANLINESS method limit/base current history1 history2 Particles >4μm ASTM D7647 >5000 298 1625 Particles >6μm ASTM D7647 >1300 70 788 Particles >14μm ASTM D7647 >160 8 114 Particles >21μm ASTM D7647 >40 2 31 Particles >38μm ASTM D7647 >10 0 4 Particles >71μm ASTM D7647 >3 0 1	Silicon	nnm	ASTM D5185(m)	>15	0	0	
Potassium ppm ASTM D5185(m) >20 <1 <1 FLUID CLEANLINESS method limit/base current history1 history2 Particles >4μm ASTM D7647 >5000 298 1625 Particles >6μm ASTM D7647 >1300 70 788 Particles >14μm ASTM D7647 >160 8 114 Particles >21μm ASTM D7647 >40 2 31 Particles >38μm ASTM D7647 >10 0 4 Particles >71μm ASTM D7647 >3 0 1			. ,	710			
$\begin{array}{cccccccccccccccccccccccccccccccccccc$. ,	>20			
Particles >6μm ASTM D7647 >1300 70 788 Particles >14μm ASTM D7647 >160 8 114 Particles >21μm ASTM D7647 >40 2 31 Particles >38μm ASTM D7647 >10 0 4 Particles >71μm ASTM D7647 >3 0 1	FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >6μm ASTM D7647 >1300 70 788 Particles >14μm ASTM D7647 >160 8 114 Particles >21μm ASTM D7647 >40 2 31 Particles >38μm ASTM D7647 >10 0 4 Particles >71μm ASTM D7647 >3 0 1	Particles >4µm		ASTM D7647	>5000	298	1625	
Particles >14μm ASTM D7647 >160 8 114 Particles >21μm ASTM D7647 >40 2 31 Particles >38μm ASTM D7647 >10 0 4 Particles >71μm ASTM D7647 >3 0 1	<u>'</u>			>1300			
Particles >21μm ASTM D7647 >40 2 31 Particles >38μm ASTM D7647 >10 0 4 Particles >71μm ASTM D7647 >3 0 1	•						
Particles >38μm ASTM D7647 >10 0 4 Particles >71μm ASTM D7647 >3 0 1	· ·						
Particles >71μm ASTM D7647 >3 0 1							
The state of the s							
			ISO 4406 (c)	>19/17/14	15/13/10	18/17/14	

Contact/Location: Robert Hicks - HANGRI



OIL ANALYSIS REPORT





CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No.

: WC0956235 : 02645880

Lab Number Unique Number : 5811432 Test Package : IND 2

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9

Received : 05 Jul 2024 **Tested** : 08 Jul 2024

Diagnosed

: 08 Jul 2024 - Kevin Marson

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

HANDLING SPECIALTY 219 SOUTH SERVICE RD.,, PO BOX 98

GRIMSBY, ON CA L3M 4G1

Contact: Robert Hicks rhicks@handling.com T: (905)945-9661

F: (905)945-0155