


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
OJ036951
Component

Diesel Engine

DIESEL ENGINE OIL SAE 40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) DIESEL ENGINE OIL SAE 40. Please confirm. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

				Jul2024		
SAMPLE INFORM	MOITAN	method				history2
Sample Number		Client Info		WC0944091		
Sample Date		Client Info		07 Jul 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
			12 21 //		111	111
CONTAMINATION	N	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>100	3		
Chromium	ppm	ASTM D5185(m)	>20	0		
Nickel	ppm	ASTM D5185(m)	>4	0		
Titanium	ppm	ASTM D5185(m)		74		
Silver	ppm	ASTM D5185(m)	>3	<1		
Aluminum	ppm	ASTM D5185(m)	>20	2		
Lead	ppm	ASTM D5185(m)	>40	0		
Copper	ppm	ASTM D5185(m)	>330	3		
Tin	ppm	ASTM D5185(m)	>15	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		<1		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	ourront	hiotoryi	history?
ADDITIVES				current	history1	history2
Boron	ppm	ASTM D5185(m)	250	134		
Barium	ppm	ASTM D5185(m)	10	0		
Molybdenum	ppm	ASTM D5185(m)	100	14		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)	450	395		
Calcium	ppm	ASTM D5185(m)	3000	1646		
Phosphorus	ppm	ASTM D5185(m)	1150	932		
Zinc	ppm	ASTM D5185(m)	1350	1077		
Sulfur	ppm	ASTM D5185(m)	4250	3096		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>25	3		
Sodium	ppm	ASTM D5185(m)	>216	2		
Potassium	ppm	ASTM D5185(m)	>20	2		
INFRA-RED		method	limit/base	current	history1	history2
	0/				,	· ·
Soot %	%	ASTM D7844*	>3	0		
Nitration	Abs/cm	ASTM D7624*	>20	5.9		
Sulfation	Abs/.1mm	ASTM D7415*	>30	18.3		



OIL ANALYSIS REPORT





CALA ISO 17025:2017 Accredited Laboratory

Laboratory

Sample No. Lab Number : 02646188 Unique Number : 5811740 Test Package : MOB 2

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 : WC0944091

Validity of results and interpretation are based on the sample and information as supplied.

Received **Tested** Diagnosed

: 09 Jul 2024 - Wes Davis

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

: 08 Jul 2024

: 09 Jul 2024

GENREP LIMITED

25 GIFFORD STREET NEPEAN, ON CA K2E 7S3

Contact: Carmen Lavryssen servicedesk@genrep.com T: (613)225-9244

F: (613)225-4690