

Area Chem-Ecol

## **OIL ANALYSIS REPORT**

SAMPLE INFORMATION method

Sample Rating Trend







A2407023 Component Unknown Component Fluid CHEM-ECOL WAYLUBE 68 L (--- GAL)

## DIAGNOSIS


## Recommendation


We certify that this oil is clean, that the additives are at acceptable levels, and that it is suitable for use.


		method	iimit/base	current	nistory i	nistoryz
Batch #		Client Info		3139-A		
Department		Client Info		Production		
Sample From		Client Info		Machine		
Production Stage		Client Info		Final		
Sent to WC		Client Info		07/05/2024		
Sample Number		Client Info		E30002585		
Sample Date		Client Info		05 Jul 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)		0		
Chromium	ppm	ASTM D5185(m)		0		
Nickel	ppm	ASTM D5185(m)		<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)		0		
Lead	ppm	ASTM D5185(m)		0		
Copper	ppm	ASTM D5185(m)		<1		
Tin	ppm	ASTM D5185(m)		0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<1		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		1		
Calcium	ppm	ASTM D5185(m)		2		
Phosphorus	ppm	ASTM D5185(m)		180		
Zinc	ppm	ASTM D5185(m)		7		
Sulfur	ppm	ASTM D5185(m)		1980		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		<1		
Sodium	ppm	ASTM D5185(m)		1		
Potassium	ppm	ASTM D5185(m)	>20	0		
Water	%	ASTM D6304*		0.001		
ppm Water	ppm	ASTM D6304*		2		



## **OIL ANALYSIS REPORT**









FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	388		
Particles >6µm		ASTM D7647	>640	113		
Particles >14µm		ASTM D7647	>160	8		
Particles >21µm		ASTM D7647	>40	2		
Particles >38µm		ASTM D7647	>10	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	16/14/10		
FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.92		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*		NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	68	69.2		
Visc @ 100°C	cSt	ASTM D7279(m)		9.6		
Viscosity Index (VI)	Scale	ASTM D2270*		118		
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color				i Y	no image	no image



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Environmental 360 Solutions Ltd. CALA : E30002585 Received : 08 Jul 2024 Sample No. 640 Victoria Street ŝ Lab Number : 02646213 Tested : 09 Jul 2024 Cobourg, ON ISO 17025:2017 Accredited Laboratory : 12 Jul 2024 - Aylwin Lee CA K9A 5H5 Unique Number : 5811765 Diagnosed Test Package : IND 2 ( Additional Tests: KF, KV100, PrtCount, VI ) Contact: Tatiana Sorkina tsorkina@e360s.ca To discuss this sample report, contact Customer Service at 1-905-372-2251. Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab. T: (800)263-3939 Validity of results and interpretation are based on the sample and information as supplied. F: (905)373-4950

Report Id: CHECOB [WCAMIS] 02646213 (Generated: 07/12/2024 07:53:02) Rev: 1

Contact/Location: Tatiana Sorkina - CHECOB

no image

no image