

OIL ANALYSIS REPORT

Area Arvin Sango - 888103 RB052

Hydraulic System Fluid CATALYS HYDRAULIC AW 46 (--- GAL)

DIAGNOSIS

Recommendation

We certify that this oil is clean, that the additives are at acceptable levels, and that it is suitable for use.

				Jui2024			
SAMPLE INFORM		ام م والد مور	lineit/leese		history of	la la tama	
	MATION	method	limit/base	current	history1	history	
Machine ID		Client Info		F12-18			
Department		Client Info		Sales			
Sample From		Client Info		Machine			
Production Stage		Client Info		Initial			
Sent to WC Sample Number		Client Info Client Info		05/07/2024 E30002567			
		Client Info		02 Jul 2024			
Sample Date	hrs	Client Info					
Machine Age		Client Info		0			
Oil Age	hrs			0 N/A			
Oil Changed		Client Info		N/A			
Sample Status				NORMAL			
WEAR METALS		method	limit/base	current	history1	history	
Iron	ppm	ASTM D5185(m)	>20	<1			
Chromium	ppm	ASTM D5185(m)	>20	0			
Nickel	ppm	ASTM D5185(m)	>20	0			
Titanium	ppm	ASTM D5185(m)		0			
Silver	ppm	ASTM D5185(m)		0			
Aluminum	ppm	ASTM D5185(m)	>20	<1			
Lead	ppm	ASTM D5185(m)	>20	0			
Copper	ppm	ASTM D5185(m)	>20	<1			
Tin	ppm	ASTM D5185(m)	>20	0			
Antimony	ppm	ASTM D5185(m)		0			
Vanadium	ppm	ASTM D5185(m)		0			
Beryllium	ppm	ASTM D5185(m)		0			
Cadmium	ppm	ASTM D5185(m)		0			
ADDITIVES		method	limit/base	current	history1	history	
Boron	ppm	ASTM D5185(m)		26			
Barium	ppm	ASTM D5185(m)		<1			
Molybdenum	ppm	ASTM D5185(m)		0			
Manganese	ppm	ASTM D5185(m)		0			
Magnesium	ppm	ASTM D5185(m)		2			
Calcium	ppm	ASTM D5185(m)		104			
Phosphorus	ppm	ASTM D5185(m)		349			
Zinc	ppm	ASTM D5185(m)		445			
Sulfur	ppm	ASTM D5185(m)		752			
Lithium	ppm	ASTM D5185(m)		<1			
CONTAMINANTS	\$	method	limit/base	current	history1	history	
Silicon	ppm	ASTM D5185(m)	>15	0			
Sodium	ppm	ASTM D5185(m)		<1			
Potassium	ppm	ASTM D5185(m)	>20	7			
Water	%	ASTM D6304*	>0.05	0.002			
ppm Water	ppm	ASTM D6304*	>500	23			


Sample Rating Trend





NORMAL




OIL ANALYSIS REPORT










FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	503		
Particles >6µm		ASTM D7647	>640	67		
Particles >14µm		ASTM D7647	>160	9		
Particles >21µm		ASTM D7647	>40	3		
Particles >38µm		ASTM D7647	>10	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	16/13/10		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.38		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.05	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	46.9	45.0		
Visc @ 100°C	cSt	ASTM D7279(m)	6.9	6.8		
Viscosity Index (VI)	Scale	ASTM D2270*	102	105		
SAMPLE IMAGES	6	method	limit/base	current	history1	history2
				12 - A		
Color					no image	no image





Report Id: CHECOB [WCAMIS] 02646224 (Generated: 07/10/2024 14:26:46) Rev: 1

Contact/Location: Tatiana Sorkina - CHECOB

no image

no image