

OIL ANALYSIS REPORT

Area Arvin Sango - 888103 RB055 Component

Hydraulic System Fluid CATALYS HYDRAULIC AW 46 (--- GAL)

DIAGNOSIS

Recommendation

We certify that this oil is clean, that the additives are at acceptable levels, and that it is suitable for use.

				Jul2024			
SAMPLE INFORM		method	limit/base	ourropt	history1	history2	
	VIATION		IIIIII/Dase			,	
Machine ID		Client Info		B44-2			
Department		Client Info		Sales			
Sample From		Client Info		Machine			
Production Stage		Client Info		Initial			
Sent to WC		Client Info		07/05/2024			
Sample Number				E30002570			
Sample Date	lava	Client Info		02 Jul 2024			
Machine Age	hrs	Client Info		0			
Oil Age	hrs	Client Info		0			
Oil Changed		Client Info		N/A			
Sample Status				NORMAL			
WEAR METALS		method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185(m)	>20	<1			
Chromium	ppm	ASTM D5185(m)	>20	0			
Nickel	ppm	ASTM D5185(m)	>20	<1			
Titanium	ppm	ASTM D5185(m)		0			
Silver	ppm	ASTM D5185(m)		0			
Aluminum	ppm	ASTM D5185(m)	>20	<1			
Lead	ppm	ASTM D5185(m)	>20	0			
Copper	ppm	ASTM D5185(m)	>20	1			
Tin	ppm	ASTM D5185(m)	>20	0			
Antimony	ppm	ASTM D5185(m)		0			
Vanadium	ppm	ASTM D5185(m)		0			
Beryllium	ppm	ASTM D5185(m)		0			
Cadmium	ppm	ASTM D5185(m)		0			
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185(m)		<1			
Barium	ppm	ASTM D5185(m)		<1			
Molybdenum	ppm	ASTM D5185(m)		0			
Manganese	ppm	ASTM D5185(m)		0			
Magnesium	ppm	ASTM D5185(m)		<1			
Calcium	ppm	ASTM D5185(m)		42			
Phosphorus	ppm	ASTM D5185(m)		316			
Zinc	ppm	ASTM D5185(m)		406			
Sulfur	ppm	ASTM D5185(m)		688			
Lithium	ppm	ASTM D5185(m)		<1			
CONTAMINANTS		method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185(m)	>15	0			
Sodium	ppm	ASTM D5185(m)		0			
Potassium	ppm	ASTM D5185(m)	>20	<1			
Water	%	ASTM D6304*		0.001			
ppm Water	ppm	ASTM D6304*	>500	6			
ppin mator	PPIII	70 FW D0004	2000	U			







NORMAL


Sample Rating Trend




OIL ANALYSIS REPORT











Color

Bottom



FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	1947		
Particles >6µm		ASTM D7647	>640	341		
Particles >14µm		ASTM D7647	>160	41		
Particles >21µm		ASTM D7647	>40	12		
Particles >38µm		ASTM D7647	>10	2		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	18/16/13		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.32		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.05	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	46.9	45.2		
Visc @ 100°C	cSt	ASTM D7279(m)	6.9	7.0		
Viscosity Index (VI)	Scale	ASTM D2270*	102	112		
SAMPLE IMAGES	\$	method	limit/base	current	history1	history2





Report Id: CHECOB [WCAMIS] 02646227 (Generated: 07/10/2024 15:13:57) Rev: 1

Contact/Location: Tatiana Sorkina - CHECOB