

## **OIL ANALYSIS REPORT**

### Area AIM Recycling Windsor - 888101 RB042-R


Component Hydraulic System Fluid PETRO CANADA HYDREX AW 46 (--- GAL)

#### DIAGNOSIS

#### Recommendation

We certify that this oil is clean, that the additives are at acceptable levels, and that it is suitable for use.

/						
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Machine ID		Client Info		Press #2		
Department		Client Info		Sales		
Sample From		Client Info		Machine		
Production Stage		Client Info		Lab Reclaim		
Sent to WC		Client Info		07/04/2024		
Sample Number		Client Info		E30002556		
Sample Date		Client Info		04 Jul 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	1		
Chromium	ppm	ASTM D5185(m)	>20	0		
Nickel	ppm	ASTM D5185(m)	>20	<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>20	<1		
Lead	ppm	ASTM D5185(m)	>20	0		
Copper	ppm	ASTM D5185(m)	>20	<1		
Tin	ppm	ASTM D5185(m)	>20	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	0	1		
Barium	ppm	ASTM D5185(m)	0	0		
Molybdenum	ppm	ASTM D5185(m)	0	0		
Manganese	ppm	ASTM D5185(m)	0	0		
Magnesium	ppm	ASTM D5185(m)	0	4		
Calcium	ppm	ASTM D5185(m)	50	73		
Phosphorus	ppm	ASTM D5185(m)	330	334		
Zinc	ppm	ASTM D5185(m)	430	430		
Sulfur	ppm	ASTM D5185(m)	760	784		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	0		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	0		
Water	%	ASTM D6304*	>0.05	0.001		
ppm Water	ppm	ASTM D6304*	>500	10		




Sample Rating Trend





NORMAL




# **OIL ANALYSIS REPORT**










FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	256		
Particles >6µm		ASTM D7647	>640	97		
Particles >14µm		ASTM D7647	>160	9		
Particles >21µm		ASTM D7647	>40	2		
Particles >38µm		ASTM D7647	>10	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	15/14/10		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.70	0.40		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.05	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	46.4	45.8		
Visc @ 100°C	cSt	ASTM D7279(m)	6.92	7.2		
Viscosity Index (VI)	Scale	ASTM D2270*	104	117		
SAMPLE IMAGES	6	method	limit/base	current	history1	history2
Color				E300029	no image	no image





Report Id: CHECOB [WCAMIS] 02646244 (Generated: 07/10/2024 10:26:16) Rev: 1

Contact/Location: Tatiana Sorkina - CHECOB

no image

no image

Page 2 of 2