




# OIL ANALYSIS REPORT

Sample Rating Trend



VISCOSITY



Area

**MINING**

Machine Id

**ME-586 JOHN DEERE 944K 1DW944KXPNL703686**

Component

**Front Right Final Drive**

Fluid

**SHELL Spirax S4 CX 30 (--- GAL)**

## DIAGNOSIS

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>WC0942058</b>	---	---
Sample Date	Client Info			<b>02 Jul 2024</b>	---	---
Machine Age	hrs	Client Info		<b>3191</b>	---	---
Oil Age	hrs	Client Info		<b>3191</b>	---	---
Oil Changed	Client Info			<b>Not Chngd</b>	---	---
Sample Status				<b>ABNORMAL</b>	---	---

CONTAMINATION		method	limit/base	current	history1	history2
Water	WC Method		>0.075	<b>NEG</b>	---	---


WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>750	<b>12</b>	---	---
Chromium	ppm	ASTM D5185(m)	>9	<b>0</b>	---	---
Nickel	ppm	ASTM D5185(m)	>10	<b>&lt;1</b>	---	---
Titanium	ppm	ASTM D5185(m)		<b>0</b>	---	---
Silver	ppm	ASTM D5185(m)		<b>&lt;1</b>	---	---
Aluminum	ppm	ASTM D5185(m)	>40	<b>&lt;1</b>	---	---
Lead	ppm	ASTM D5185(m)	>15	<b>&lt;1</b>	---	---
Copper	ppm	ASTM D5185(m)	>40	<b>32</b>	---	---
Tin	ppm	ASTM D5185(m)	>10	<b>0</b>	---	---
Antimony	ppm	ASTM D5185(m)	>5	<b>0</b>	---	---
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	---	---
Beryllium	ppm	ASTM D5185(m)		<b>0</b>	---	---
Cadmium	ppm	ASTM D5185(m)		<b>0</b>	---	---

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<b>3</b>	---	---
Barium	ppm	ASTM D5185(m)		<b>&lt;1</b>	---	---
Molybdenum	ppm	ASTM D5185(m)		<b>&lt;1</b>	---	---
Manganese	ppm	ASTM D5185(m)		<b>&lt;1</b>	---	---
Magnesium	ppm	ASTM D5185(m)		<b>52</b>	---	---
Calcium	ppm	ASTM D5185(m)		<b>3156</b>	---	---
Phosphorus	ppm	ASTM D5185(m)		<b>1095</b>	---	---
Zinc	ppm	ASTM D5185(m)		<b>1219</b>	---	---
Sulfur	ppm	ASTM D5185(m)		<b>3428</b>	---	---
Lithium	ppm	ASTM D5185(m)		<b>&lt;1</b>	---	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>75	<b>26</b>	---	---
Sodium	ppm	ASTM D5185(m)	>51	<b>2</b>	---	---
Potassium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	---	---



# OIL ANALYSIS REPORT






VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	Visual*	NONE	NONE	---	---
Yellow Metal	scalar	Visual*	NONE	NONE	---	---
Precipitate	scalar	Visual*	NONE	NONE	---	---
Silt	scalar	Visual*	NONE	NONE	---	---
Debris	scalar	Visual*	NONE	NONE	---	---
Sand/Dirt	scalar	Visual*	NONE	NONE	---	---
Appearance	scalar	Visual*	NORML	NORML	---	---
Odor	scalar	Visual*	NORML	NORML	---	---
Emulsified Water	scalar	Visual*	>0.075	NEG	---	---
Free Water	scalar	Visual*		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 40°C	cSt	ASTM D7279(m)	93.9	▲ 47.4	---	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------

Color				no image	no image
Bottom				no image	no image

## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : WC0942058      **Received** : 08 Jul 2024  
**Lab Number** : 02646354      **Tested** : 08 Jul 2024  
**Unique Number** : 5811906      **Diagnosed** : 09 Jul 2024 - Kevin Marson  
**Test Package** : CONST

**Covia Canada Ltd.**  
 260 Unimin Road, County Rd. #46  
 Havelock, ON  
 CA K0L 1Z0  
 Contact: Dan Lyon  
 dan.lyon@coviacorp.com  
 T: (705)632-8904  
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.