

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

BALER DBR-42-LA Component Hydraulic System Fluid SAE 5W20 (--- GAL)

DIAGNOSIS

Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. The filter change at the time of sampling has been noted. Confirm the source of the lubricant being utilized for top-up/fill. Resample at the next service interval to monitor. The fluid was specified as (GENERIC) SAE 5W20, however, a fluid match indicates that this fluid is ISO 32 AW Hydraulic Oil. Please confirm the oil type and grade on your next sample. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is a light amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

Viscosity of sample indicates oil is within ISO 32 range, advise investigate. This plus the additive levels indicates that this is not the same brand, or type of oil as reported. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	current history1	
Sample Number		Client Info		WC0946963		
Sample Date		Client Info		11 Jul 2024		
Machine Age	yrs	Client Info		1		
Oil Age	yrs	Client Info		1		
Oil Changed		Client Info		Changed		
Sample Status				ABNORMAL		
CONTAMINATION	1	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	6		
Chromium	ppm	ASTM D5185(m)	>10	0		
Nickel	ppm	ASTM D5185(m)	>10	<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>10	<1		
Lead	ppm	ASTM D5185(m)	>10	0		
Copper	ppm	ASTM D5185(m)	>75	1		
Tin	ppm	ASTM D5185(m)	>10	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<1		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		2		
Calcium	ppm	ASTM D5185(m)		<mark> </mark> 59		
Phosphorus	ppm	ASTM D5185(m)		e 226		
Zinc	ppm	ASTM D5185(m)		<mark> </mark> 275		
Sulfur	ppm	ASTM D5185(m)		1436		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>20	<1		
Sodium	ppm	ASTM D5185(m)		1		
Potassium	ppm	ASTM D5185(m)	>20	<1		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	9333		
Particles >6µm		ASTM D7647	>1300	<u> </u>		
Particles >14µm		ASTM D7647	>160	<mark>)</mark> 218		
Particles >21µm		ASTM D7647	>40	63		
Particles >38µm		ASTM D7647	>10	5		
Particles >71µm		ASTM D7647	>3	1		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	0 20/18/15		
:33:17) Rev: 1				Contact/Locatio	n: Jeremy Kozio	I - CON266MIS Page 1 of 2



OIL ANALYSIS REPORT

Particle Trend			FLUID DEGRAD	ATION	method	limit/base	current	history1	history2
Ξ 8k - 4μm			Acid Number (AN)	mg KOH/g	ASTM D974*		0.25		
2 6k			VISUAI		method	limit/base	current	history1	history2
Abnormal				a a a la v	Viewel*		NONE	motory	motoryz
			White Metal	scalar	Visual*	NONE	NONE		
2 2k -		*****	Precipitate	scalar	Visual*	NONE	NONE		
0k		24	Silt	scalar	Visual*	NONE	NONE		
/11/n/		/111/	Debris	scalar	Visual*	NONE	NONE		
			Sand/Dirt	scalar	Visual*	NONE	NONE		
Additives			Appearance	scalar	Visual*	NORML	NORML		
300 - calcium			Odor	scalar	Visual*	NORML	NORML		
250 -			Emulsified Water	scalar	Visual*	>0.1	NEG		
Ē 200 -		*****	Free Water	scalar	Visual*		NEG		
150-			FLUID PROPER	TIES	method	limit/base	current	history1	history2
100			Visc @ 40°C	cSt	ASTM D7279(m)	43.0	4 32.1		
ul11/24		ul11/24	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Particle Trend 10k			Color					no image	no image
Abnormal Abnormal Abnormal Abnormal			Bottom					no image	no image
Additives		∲C = 5 17"	Ferrous Alloys			491,52 122,88 30,72 127,88 7,68 7,68 1,92	Particle Count		-24 -22 -20 -20 -20 -20 -20 -20 -20 -20 -20 -20 -20 -20 -20 -20 -20 -20 -21 -24 -24 -24 -24 -24 -24 -24 -24 -24 -24
Acid Number		1	Non-ferrous Meta	ls		48 48 48 42 42 42 42 42 42 42 42 42 42 42 42 42	10 - 10 - 8 - 2 -		16 Cleanfiness Code 14 14 12 10 10 10 10 10 10 10 10 10 10 10 10 10
0.00 (0)0.24 0)100 00.18 0.18 0.10 0.00 0		111 D 8	Viscosity @ 40°C			-7 0.0.3 9.0.0 Winnber (mg K0H/0) 9.0.0 Add Number (mg K0H/0) 9.0 Add	0.4μ Acid Number	14µ 21µ	38μ 71μ
	COCALLA ISO 17025:2017 Accredited Laboratory To discuss this sau Test denoted (*) ou Validity of results a	boratory mple No. b Number ique Number st Package mple report, utside scope and interpret	: WearCheck - C8-117 : WC0946963 : 02647829 : 5813381 : IND 2 contact Customer Serve of accreditation, (m) n ration are based on the	5 Appleby Rece Teste Diagr vice at 1-8 nethod mo sample a	y Line, Burlin ived : 15 id : 16 nosed : 16 200-268-213 podified, (e) te nd informatic	gton, ON L7 5 Jul 2024 5 Jul 2024 Jul 2024 - Kev 1. sted at exter on as supplie	rL 5H9 C(2660 MEA) vin Marson rnal Iab. ed.	DNESTOGA CO DOWPINE BLVD,, DOO MISS Contact: jkoziol@ca T: F:	LD STORAGE R57, CALL EXT. 2317 ISSAUGA, ON CA L5N 7E6 Jeremy Koziol oldstorage.com (519)748-4086 (905)567-1844

Report Id: CON266MIS [WCAMIS] 02647829 (Generated: 07/16/2024 10:33:17) Rev: 1

Contact/Location: Jeremy Koziol - CON266MIS