

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Machine Id

SHUTTLE CONVEYOR PT SID

Component Gearbox

Fluid MOBIL MOBILGEAR SHC 320 (17 LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0707870		
Sample Date		Client Info		15 Jul 2024		
Machine Age	mths	Client Info		0		
Oil Age	mths	Client Info		12		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184*		0		
Iron	ppm	ASTM D5185(m)	>200	4		
Chromium	ppm	ASTM D5185(m)	>10	0		
Nickel	ppm	ASTM D5185(m)	>10	<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>25	<1		
Lead	ppm	ASTM D5185(m)	>50	0		
Copper	ppm	ASTM D5185(m)	>200	0		
Tin	ppm	ASTM D5185(m)	>10	0		
Antimony	ppm	ASTM D5185(m)	>5	<1		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		3		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		0		
Calcium	ppm	ASTM D5185(m)		2		
Phosphorus	ppm	ASTM D5185(m)		423		
Zinc	ppm	ASTM D5185(m)		2		
Sulfur	ppm	ASTM D5185(m)		1845		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	6	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>50	18		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	<1		
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.85		



OIL ANALYSIS REPORT





White Metal Yellow Metal		method	limit/base	current	history1	history2
Yellow Metal	scalar	Visual*	NONE	VLITE		
	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	VLITE		
Sand/Dirt		Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.2	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	320	319		
SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image
GRAPHS						
Ferrous Alloys				PQ		
10 iron 1			220			
o - chromium			200	Severe		
			180	+		
2			160			
0			140			
Jul 15,24			120 Juli 2/3			
-			ੀ ਟ 100	Abnormal		
Non-ferrous Metal	s					
8 copper						
E 6-			60			
			40	1		
2			20			
2/24			5/24	724		
Jui15/24			Jul15/24	Jul15/24		
Viscosity @ 40°C 360 T Abnormal			1.0	Acid Number		
340-			(B/HO 8	I		
Go 49 320 - Base 3320 - Base			<u>ال</u> 0.6			
			a 0.4	+		
300 Abnormal			(B)HO0 0.8 (B)HO0 0.8 (B) HO0 0.8 (B) HO0 0.8 (B) HO0 0.2 (B) HO0 0.2 (B) HO0 0.2 (B) HO0 0.2 (B) HO0 0.2 (B) HO0 0.8 (B) HO0			
280			0.0	-		
Juil 5/24			Jul15/24	Jul15/24		



Test Package : IND 2 (Additional Tests: TAN Man) To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

jonathanjeffrey@savageservices.com T: (902)625-3558 F: (902)625-2446 Contact/Location: Jonathan Jeffrey - SAVPOI

Report Id: SAVPOI [WCAMIS] 02648211 (Generated: 07/17/2024 16:29:37) Rev: 1

Page 2 of 2