




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
MVR-03 WP29
 Component
Hydraulic System
 Fluid
{not provided} (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the component. The amount and size of particulates present in the system is acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

| | method | limit/base | current | history1 | history2 |
|---------------|-------------|-------------|--------------------|-------------|----------|
| Sample Number | Client Info | | WCI2257771 | WCI2243313 | --- |
| Sample Date | Client Info | | 16 Oct 2015 | 02 Jan 2013 | --- |
| Machine Age | hrs | Client Info | 0 | 0 | --- |
| Oil Age | hrs | Client Info | 0 | 0 | --- |
| Oil Changed | Client Info | | N/A | N/A | --- |
| Sample Status | | | NORMAL | SEVERE | --- |

WEAR METALS

| | method | limit/base | current | history1 | history2 |
|----------|--------|-----------------|--------------|----------|----------|
| Iron | ppm | ASTM D5185m >20 | 1 | 1 | --- |
| Chromium | ppm | ASTM D5185m >20 | 0 | <1 | --- |
| Nickel | ppm | ASTM D5185m >20 | 0 | <1 | --- |
| Titanium | ppm | ASTM D5185m | 0 | 0 | --- |
| Silver | ppm | ASTM D5185m | 0 | <1 | --- |
| Aluminum | ppm | ASTM D5185m >20 | 0 | 0 | --- |
| Lead | ppm | ASTM D5185m >20 | 0 | 1 | --- |
| Copper | ppm | ASTM D5185m >20 | <1 | 2 | --- |
| Tin | ppm | ASTM D5185m >20 | 1 | 0 | --- |
| Antimony | ppm | ASTM D5185m | 0 | 0 | --- |
| Vanadium | ppm | ASTM D5185m | 0 | 0 | --- |
| Cadmium | ppm | ASTM D5185m | 0 | <1 | --- |

ADDITIVES

| | method | limit/base | current | history1 | history2 |
|------------|--------|-------------|-------------|----------|----------|
| Boron | ppm | ASTM D5185m | 0 | 2 | --- |
| Barium | ppm | ASTM D5185m | 0 | <1 | --- |
| Molybdenum | ppm | ASTM D5185m | 0 | 0 | --- |
| Manganese | ppm | ASTM D5185m | 0 | <1 | --- |
| Magnesium | ppm | ASTM D5185m | 0 | 2 | --- |
| Calcium | ppm | ASTM D5185m | 87 | 124 | --- |
| Phosphorus | ppm | ASTM D5185m | 437 | 595 | --- |
| Zinc | ppm | ASTM D5185m | 657 | 807 | --- |
| Sulfur | ppm | ASTM D5185m | 4143 | 5153 | --- |

CONTAMINANTS

| | method | limit/base | current | history1 | history2 |
|-----------|--------|-----------------|----------|----------|----------|
| Silicon | ppm | ASTM D5185m >15 | 0 | 1 | --- |
| Sodium | ppm | ASTM D5185m | 8 | 5 | --- |
| Potassium | ppm | ASTM D5185m >20 | 7 | 13 | --- |

FLUID CLEANLINESS





| | method | limit/base | current | history1 | history2 |
|-----------------|--------------|------------|-----------------|------------|----------|
| Particles >4µm | ASTM D7647 | >5000 | 7723 | 5658 | --- |
| Particles >6µm | ASTM D7647 | >1300 | 738 | ▲ 3082 | --- |
| Particles >14µm | ASTM D7647 | >160 | 122 | ▲ 525 | --- |
| Particles >21µm | ASTM D7647 | >40 | 40 | ▲ 177 | --- |
| Particles >38µm | ASTM D7647 | >10 | 3 | ▲ 27 | --- |
| Particles >71µm | ASTM D7647 | >3 | 0 | ▲ 2 | --- |
| Oil Cleanliness | ISO 4406 (c) | >19/17/14 | 20/17/14 | ▲ 20/19/16 | --- |

FLUID DEGRADATION

| | method | limit/base | current | history1 | history2 |
|------------------|----------|------------|-------------|----------|----------|
| Acid Number (AN) | mg KOH/g | ASTM D8045 | 1.01 | 1.16 | --- |



OIL ANALYSIS REPORT








| VISUAL | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | --- |
| Yellow Metal | scalar | *Visual | NONE | NONE | --- |
| Precipitate | scalar | *Visual | NONE | NONE | --- |
| Silt | scalar | *Visual | NONE | NONE | --- |
| Debris | scalar | *Visual | NONE | NONE | --- |
| Sand/Dirt | scalar | *Visual | NONE | NONE | --- |
| Appearance | scalar | *Visual | NORML | NORML | ▲ HAZY |
| Odor | scalar | *Visual | NORML | NORML | --- |
| Emulsified Water | scalar | *Visual | >0.05 | NEG | ● 5.0% |
| Free Water | scalar | *Visual | | NEG | ● 5.0 |

| FLUID PROPERTIES | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| Visc @ 40°C | cSt | ASTM D445 | 46.26 | 47.9 | --- |

| SAMPLE IMAGES | method | limit/base | current | history1 | history2 |
|---------------|--------|------------|---------|----------|----------|
|---------------|--------|------------|---------|----------|----------|

| | | | | | | |
|--------|--|--|--|----------|----------|----------|
| Color | | | | no image | no image | no image |
| Bottom | | | | no image | no image | no image |

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC12257771 **Received** : 23 Oct 2015
Lab Number : 03850287 **Diagnosed** : 27 Oct 2015
Unique Number : 7185505 **Diagnostician** : Jonathan Hester
Test Package : IND 2

LEPRINO FOODS-ROSWELL
 5600 OMAHA RD
 ROSWELL, NM
 US 88203
 Contact: JOAQUIN NIETO
 jnieto@leprinofoods.com
 T:
 F: (505)347-5728

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)