


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
66316 (S/N 61016142)
 Component
Hydraulic System
 Fluid
AW HYDRAULIC OIL ISO 46 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the component. The amount and size of particulates present in the system is acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			RP194016	RP181422	RP177683
Sample Date	Client Info			13 Mar 2019	11 Mar 2018	08 Aug 2017
Machine Age	mths	Client Info		0	0	0
Oil Age	mths	Client Info		0	0	0
Oil Changed	Client Info			N/A	N/A	N/A
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	8	6	6
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1
Nickel	ppm	ASTM D5185m	>20	<1	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	<1	0	0
Lead	ppm	ASTM D5185m	>20	<1	<1	0
Copper	ppm	ASTM D5185m	>20	6	▲ 87	5
Tin	ppm	ASTM D5185m	>20	<1	<1	<1
Antimony	ppm	ASTM D5185m		0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0






ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	5	<1	<1	<1
Barium	ppm	ASTM D5185m	5	<1	0	<1
Molybdenum	ppm	ASTM D5185m	5	<1	<1	0
Manganese	ppm	ASTM D5185m		<1	<1	0
Magnesium	ppm	ASTM D5185m	25	5	3	6
Calcium	ppm	ASTM D5185m	200	120	123	121
Phosphorus	ppm	ASTM D5185m	300	426	454	445
Zinc	ppm	ASTM D5185m	370	544	536	558

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	1	<1	1
Sodium	ppm	ASTM D5185m		2	3	2
Potassium	ppm	ASTM D5185m	>20	1	1	<1
Water	%	ASTM D6304	>0.05	0.006	0.007	0.024
ppm Water	ppm	ASTM D6304	>500	60	70	240

FLUID CLEANLINESS		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	1045	2390	668
Particles >6µm		ASTM D7647	>1300	278	921	184
Particles >14µm		ASTM D7647	>160	22	104	24
Particles >21µm		ASTM D7647	>40	5	23	9
Particles >38µm		ASTM D7647	>10	0	1	6
Particles >71µm		ASTM D7647	>3	0	0	6
Oil Cleanliness		ISO 4406 (c)	>19/17/14	17/15/12	18/17/14	17/15/12

FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.57	0.847	0.800	0.826


OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	VLITE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	VLITE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445 46	43.4	43.42	43.19

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RP194016 **Received** : 14 Mar 2019
Lab Number : **04670307** **Diagnosed** : 15 Mar 2019
Unique Number : 8526813 **Diagnostician** : Don Baldrige
Test Package : IND 2

YANFENG GLOBAL INTERIORS
 42150 EXECUTIVE DR
 HARRISON TWP, MI
 US 48045
 Contact: RYAN FRANK
 ryan.frank01@yanfeng.com
 T: (586)638-8350
 F: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)