


OIL ANALYSIS REPORT

3521-A EVAPORATOR

Component Gearbox

MOBIL MOBILGEAR 600 XP ISO 150 (15 QTS)





Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: Cleaned oil in gearbox with oil filtration cart due to last oil sample result. Resampled.)

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| (15) | | Aug201 | 9 Feb 2020 | Apr2020 A | pr2020 | |
|------------------|----------|--------------|------------|-------------|-------------------|-------------------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | WC0425052 | WC0425049 | WC0425043 |
| Sample Date | | Client Info | | 27 Apr 2020 | 17 Apr 2020 | 24 Feb 2020 |
| Machine Age | hrs | Client Info | | 0 | 0 | 0 |
| Oil Age | hrs | Client Info | | 100 | 60 | 150 |
| Oil Changed | | Client Info | | Not Changd | Not Changd | Not Changd |
| Sample Status | | | | NORMAL | ABNORMAL | SEVERE |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >200 | 2 | 11 | 5 12 |
| Chromium | ppm | ASTM D5185m | >15 | <1 | <1 | 5 |
| Nickel | ppm | ASTM D5185m | >15 | 0 | <1 | 3 |
| Titanium | ppm | ASTM D5185m | | 0 | 0 | 1 |
| Silver | ppm | ASTM D5185m | | <1 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >25 | 0 | 0 | 2 |
| Lead | ppm | ASTM D5185m | >100 | <1 | 0 | 2 |
| Copper | ppm | ASTM D5185m | >200 | <1 | <1 | <1 |
| Tin | ppm | ASTM D5185m | >25 | 0 | 0 | 0 |
| Antimony | ppm | ASTM D5185m | | 3 | 8 | 207 |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 25 | 23 | 21 |
| Barium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | | <1 | 0 | <1 |
| Manganese | ppm | ASTM D5185m | | <1 | <1 | 6 |
| Magnesium | ppm | ASTM D5185m | | <1 | 0 | 1 |
| Calcium | ppm | ASTM D5185m | | <1 | <1 | 3 |
| Phosphorus | ppm | ASTM D5185m | | 327 | 300 | 361 |
| Zinc | ppm | ASTM D5185m | | 0 | 2 | 3 |
| Sulfur | ppm | ASTM D5185m | | 13649 | 12476 | 14638 |
| CONTAMINANTS | ; | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >50 | 2 | <1 | 4 |
| Sodium | ppm | ASTM D5185m | | 1 | <1 | 4 |
| Potassium | ppm | ASTM D5185m | >20 | <1 | 4 | 10 |
| Water | % | ASTM D6304 | >0.2 | 0.010 | 0.010 | 0.007 |
| ppm Water | ppm | ASTM D6304 | >2000 | 106.1 | 105.1 | 70.6 |
| FLUID CLEANLIN | IESS | method | limit/base | current | history1 | history2 |
| Particles >4µm | | ASTM D7647 | >20000 | 12368 | <u></u> 65381 | ▲ 382771 |
| Particles >6µm | | ASTM D7647 | >5000 | 1298 | 8997 | <u>▲</u> 55783 |
| Particles >14µm | | ASTM D7647 | >640 | 50 | 244 | 570 |
| Particles >21µm | | ASTM D7647 | >160 | 11 | 46 | 143 |
| Particles >38µm | | ASTM D7647 | >40 | 2 | 4 | 3 |
| Particles >71µm | | ASTM D7647 | >10 | 1 | 0 | 0 |
| Oil Cleanliness | | ISO 4406 (c) | >21/19/16 | 21/17/13 | △ 23/20/15 | <u>△</u> 26/23/16 |
| FLUID DEGRADA | ATION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.754 | 0.745 | 0.669 |



OIL ANALYSIS REPORT

