


OIL ANALYSIS REPORT

TEC 10K [12221140] ATLAS COPCO CAI486821 - TODD JUDY FORD

Component

Compressor





Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| | | Nov2019 | May2020 Oct2020 | Apr2021 Jul2021 | Nov2021 | |
|------------------|----------|-----------------|-----------------|-----------------|-------------|-------------|
| SAMPLE INFORM | MOITAN | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | UCH05402445 | UCH05328627 | UCH05233731 |
| Sample Date | | Client Info | | 08 Nov 2021 | 27 Jul 2021 | 13 Apr 2021 |
| Machine Age | hrs | Client Info | | 30996 | 39152 | 28221 |
| Oil Age | hrs | Client Info | | 7678 | 5861 | 4908 |
| Oil Changed | | Client Info | | Changed | Not Changd | Not Changd |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 0 | <1 | <1 |
| Chromium | ppm | ASTM D5185m | >5 | <1 | <1 | 0 |
| Nickel | ppm | ASTM D5185m | | 0 | <1 | <1 |
| Titanium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185m | | <1 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >15 | 0 | 0 | <1 |
| Lead | ppm | ASTM D5185m | >65 | <1 | 0 | 2 |
| Copper | ppm | ASTM D5185m | | <1 | <1 | - <1 |
| Tin | ppm | ASTM D5185m | >10 | <1 | <1 | 0 |
| Antimony | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Cadmium | | ASTM D5185m | | 0 | 0 | <1 |
| Gaumum | ppm | HOTIVI DOTODIII | | U | U | < 1 |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | <1 | <1 | 0 |
| Barium | ppm | ASTM D5185m | | <1 | <1 | <1 |
| Molybdenum | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Manganese | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Magnesium | ppm | ASTM D5185m | | <1 | 0 | 0 |
| Calcium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Phosphorus | ppm | ASTM D5185m | | 243 | 248 | 152 |
| Zinc | ppm | ASTM D5185m | | 101 | 83 | 0 |
| Sulfur | ppm | ASTM D5185m | | 246 | 264 | 661 |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >35 | <1 | 1 | <1 |
| Sodium | ppm | ASTM D5185m | | 3 | 3 | <1 |
| Potassium | ppm | ASTM D5185m | >20 | <1 | <1 | 0 |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.438 | 0.374 | 0.179 |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Precipitate | scalar | *Visual | NONE | NONE | NONE | NONE |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | NEG | NEG |
| | Juaiai | vioual | /U. I | 1124 | INLU | INLU |


ntaction: ? ? - NEGOTSAI


NEG




OIL ANALYSIS REPORT













Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 9746608 Test Package : IND 2

: UCH05402445 : 05402445

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 16 Nov 2021 Diagnosed : 19 Nov 2021 Diagnostician : Angela Borella

TOTAL EQUIPMENT COMPANY

200 SMILEY DR SAINT ALBANS, WV US 25177

49.0

Contact:

T:

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)