

GREASE ANALYSIS

DAKOTA RANGE III [200006928] 03WEA87772 - A-03

Component

Front Grease

any contamination in the grease.

MOBIL SHC GREASE 460 WT (--- LTR)

Sample Rating Trend



,					Feb 2022	
DIAGNOSIS	SAMPLE INFORM	MATION	method	limit/base	current	ŀ
Recommendation	Sample Number		Client Info		NX05576089	
Resample at the next service interval to monitor.	Sample Date		Client Info		07 Feb 2022	
Wear	Machine Age	hrs	Client Info		4229	
All component wear rates are normal.	Grease Age	hrs	Client Info		0	
Grease Condition	Grease Serviced		Client Info		N/A	
The condition of the greases additive package is	Sample Status				NORMAL	
suitable for further service.	WEAR METALS		method	limit/base	current	ł
Contaminants Insufficient sample was received to conduct all the	Iron	ppm	ASTM D5185m	>250	17	
routine laboratory tests. There is no indication of	Chromium	ppm	ASTM D5185m	>10	0	
, , , , ,					_	

Campio Hamboi		Onone inio		11710007 0000		
Sample Date		Client Info		07 Feb 2022		
Machine Age	hrs	Client Info		4229		
Grease Age	hrs	Client Info		0		
Grease Serviced		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>250	17		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m	>5	0		
Cadmium	ppm	ASTM D5185m		<1		
Titanium	ppm	ASTM D5185m		0		
Vanadium	ppm	ASTM D5185m		<1		
Lead	ppm	ASTM D5185m	>25	<1		
Copper	ppm	ASTM D5185m	>75	24		
Tin	ppm	ASTM D5185m	>5	4		
Silver	ppm	ASTM D5185m	>5	1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		54		
Magnesium	ppm	ASTM D5185m		1		
Manganese	ppm	ASTM D5185m		<1		
Molybdenum	ppm	ASTM D5185m		1022		
Phosphorus	ppm	ASTM D5185m		422		
Zinc	ppm	ASTM D5185m		22		
THICKENER/SO	AP	method	limit/base	current	history1	history2
Aluminum	ppm	ASTM D5185m		4		
Barium	ppm	ASTM D5185m		4		
Calcium	ppm	ASTM D5185m		11		
Sodium	ppm	ASTM D5185m		27		
Lithium	ppm	ASTM D5185m		2018		
Sulfur	ppm	ASTM D5185m		1660		
CONTAMINANTS	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>150	117		
***	le le					


Sodium	ppm	ASTM D5185m		27		
Lithium	ppm	ASTM D5185m		2018		
Sulfur	ppm	ASTM D5185m		1660		
CONTAMINANTS	3	method	limit/base	current	history1	history2
			450	44=		
Silicon	ppm	ASTM D5185m	>150	117		
Silicon Potassium	ppm	ASTM D5185m ASTM D5185m	>150	11 <i>7</i> 2		
	ppm		>150 limit/base			

GREASE CONDI	TION	method			history2
Grease Color		*Visual	Red	Yellow	
Texture		*In-house		Buttery	
NLGI Consistency	NLGI Scale	*SKF Method	1.5	2	




GREASE ANALYSIS

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color				no image	no image
Bottom				no image	no image
PrtFilter			no image	no image	no image



Non-ferrous Metals







Laboratory Sample No. Lab Number

: NX05576089 : 05576089 Unique Number : 10025506

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received

Diagnosed Test Package : GRS 1 (Additional Tests: KV40, SCREEN)

: 23 Jun 2022 : 05 Jul 2022 Diagnostician : Doug Bogart

NORDEX USA - Chicago 300 SOUTH WACKER DRIVE, SUITE 1500 CHICAGO, IL

US 60606 Contact: DEVIN LINEHAN

DLinehan@nordex-online.com T: (312)386-4124

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (312)386-7102

Contact/Location: DEVIN LINEHAN - NORDEX