

OIL ANALYSIS REPORT

Fež2117 Muž2117 Aug2011 Fez2108 Aug2018 Muž2119 Seg2019 Verd021 Jund022

Sample Rating Trend



NORMAL

KAESER CSD 75T 3089130 (S/N 1104)

Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCP51922	KCP11965	KCP23683
Sample Date		Client Info		23 Jun 2022	05 Nov 2021	16 Sep 2019
Machine Age	hrs	Client Info		22418	22377	19745
Oil Age	hrs	Client Info		0	0	4002
Oil Changed		Client Info		Not Changd	Changed	Not Changd
Sample Status				NORMAL	NORMAL	ATTENTION
-	_		l'act /b a co			
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	2	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	<1	1	0
Lead	ppm	ASTM D5185m	>10	<1	0	0
Copper	ppm	ASTM D5185m	>50	2	7	11
Tin	ppm	ASTM D5185m	>10	<1	<1	0
Antimony	ppm	ASTM D5185m			0	2
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	41	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m	90	62	32	2
Calcium	ppm	ASTM D5185m		1	0	0
Phosphorus	ppm	ASTM D5185m	-	11	2	0
Zinc	ppm	ASTM D5185m		10	32	23
Sulfur	ppm	ASTM D5185m		21472	15971	10118
			limit/booo			
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	<1	<1
Sodium	ppm	ASTM D5185m		4	12	<1
Potassium	ppm	ASTM D5185m	>20	2	0	<1
Water	%	ASTM D6304		0.044	0.017	0.006
ppm Water	ppm	ASTM D6304	>500	442.8	172.5	64.5
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		268	7801	4915
Particles >6µm		ASTM D7647	>1300	87	773	1276
Particles >14µm		ASTM D7647	>80	9	34	1 05
Particles >21µm		ASTM D7647	>20	3	12	1 28
Particles >38µm		ASTM D7647	>4	0	0	3
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	15/14/10	17/12	▲ 17/14
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.43	0.325	0.340
	5 0		~			


Report Id: ZODCAL [WUSCAR] 05588268 (Generated: 12/22/2023 00:44:43) Rev: 1


Contact/Location: DONOVAN KNIGHT - ZODCAL



OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	VLITE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	43.9	45.2	44.3
SAMPLE IMAGES	3	method	limit/base	current	history1	history2
Color						
Bottom					\bigcirc	

