

OIL ANALYSIS REPORT

Sample Rating Trend

ISO



1432799 (S/N 3612857)

Component

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

						\
			May2021	Jul2022		
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCP51543	KCP35537	
Sample Date		Client Info		14 Jul 2022	26 May 2021	
Machine Age	hrs	Client Info		64583	59063	
Oil Age	hrs	Client Info		3000	0	
Oil Changed	0	Client Info		Changed	Changed	
Sample Status				ABNORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	2	2	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	<1	0	
Aluminum	ppm	ASTM D5185m	>10	<1	<1	
Lead	ppm	ASTM D5185m	>10	<1	<1	
Copper	ppm	ASTM D5185m	>50	2	<1	
Tin	ppm	ASTM D5185m	>10	0	0	
Antimony	ppm	ASTM D5185m	>10		0	
Vanadium		ASTM D5185m		0	0	
	ppm			-		
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	<1	18	
Barium	ppm	ASTM D5185m	90	0	0	
Molybdenum	ppm	ASTM D5185m	0	0	<1	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m	100	5	40	
Calcium	ppm	ASTM D5185m	0	0	0	
Phosphorus	ppm	ASTM D5185m	0	11	<1	
Zinc	ppm	ASTM D5185m	0	17	14	
Sulfur	ppm	ASTM D5185m	23500	22194	18708	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	<1	
Sodium	ppm	ASTM D5185m		1	10	
Potassium	ppm	ASTM D5185m	>20	0	5	
Water	%	ASTM D6304	>0.05	0.006	0.023	
ppm Water	ppm	ASTM D6304	>500	65.4	236.5	
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		23155	14755	
Particles >6µm		ASTM D7647	>1300	5985	<u>^</u> 2258	
Particles >14µm		ASTM D7647	>80	^ 505	<u>^</u> 200	
Particles >21µm		ASTM D7647	>20	<u> </u>	<u>^</u> 62	
Particles >38µm		ASTM D7647	>4	<u>^</u> 12	3	
Particles >71µm		ASTM D7647	>3	1	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>^</u> 22/20/16	▲ 18/15	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

0.377



OIL ANALYSIS REPORT



To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

jpadilla@dancomachine.com

T: F: