

OIL ANALYSIS REPORT

Sample Rating Trend





Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the component. The amount and size of particulates present in the system is acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


		Jun2019	Jan2020 Nov2020	Jun2021 Jan2022	Aug2022	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCP50208	KCP34582	KCP21175
Sample Date		Client Info		09 Aug 2022	20 Jan 2022	28 Jun 2021
Machine Age	hrs	Client Info		29561	24786	19891
Oil Age	hrs	Client Info		9670	4895	5518
Oil Changed		Client Info		Changed	Not Changd	Changed
Sample Status				NORMAL	ATTENTION	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	0
Chromium	ppm	ASTM D5185m		0	0	0
Nickel	ppm	ASTM D5185m	>3	<1	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver		ASTM D5185m	>2	0	0	0
	ppm			-	0	
Aluminum	ppm	ASTM D5185m	>10	0		<1
Lead	ppm	ASTM D5185m	>10	0	0	<1
Copper	ppm	ASTM D5185m		12	7	25
Tin	ppm	ASTM D5185m	>10	<1	0	2
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	0	<1	12
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m	90	0	7	54
Calcium	ppm	ASTM D5185m	2	0	0	<1
Phosphorus	ppm	ASTM D5185m		0	2	7
Zinc	ppm	ASTM D5185m		0	0	13
Sulfur	ppm	ASTM D5185m		12992	15697	16863
			1' 't /l			
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	<1	<1
Sodium	ppm	ASTM D5185m		2	0	13
Potassium	ppm	ASTM D5185m	>20	<1	0	1
Water	%	ASTM D6304	>0.05	0.00	0.008	0.024
ppm Water	ppm	ASTM D6304	>500	0.00	86.0	248.6
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		1127	13824	
Particles >6µm		ASTM D7647	>1300	400	2198	
Particles >14µm		ASTM D7647	>80	24	106	
Particles >21µm		ASTM D7647	>20	5	0 30	
Particles >38µm		ASTM D7647	>4	0	3	
Particles >71µm		ASTM D7647	>3	0	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	17/16/12	18/14	
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.42	0.42	0.380
:09:49) Rev: 1	Contact/Location: LARRY MILLER - HUHALBA					


Report Id: HUHALBAL [WUSCAR] 05616430 (Generated: 03/05/2024 05:09:49) Rev: 1


Contact/Location: LARRY MILLER - HUHALBAL



OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	MODER
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	VLITE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	44.5	44.4	44.7
SAMPLE IMAGES	5	method	limit/base	current	history1	history2
Color						
Bottom						126:

