


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL

Machine Id KAESER AS 25 4384225 (S/N 1027)

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		May2019	Nov2019	Apr2020 Jan2022	Aug2022	
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCP49330	KCP48543	KCP20659
Sample Date		Client Info		15 Aug 2022	11 Jan 2022	21 Apr 2020
Machine Age	hrs	Client Info		26543	25063	20727
Oil Age	hrs	Client Info		1480	2951	0
Oil Changed		Client Info		Changed	Changed	Not Changd
Sample Status				NORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	<1	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	<1
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	<1	<1	<1
Lead	ppm	ASTM D5185m	>10	<1	<1	<1
Copper	ppm	ASTM D5185m	>50	6	8	3
Tin	ppm	ASTM D5185m	>10	0	<1	0
Antimony	ppm	ASTM D5185m			0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	1	0	<1
Barium	ppm	ASTM D5185m	90	0	0	25
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	100	23	14	59
Calcium	ppm	ASTM D5185m	0	0	0	3
Phosphorus	ppm	ASTM D5185m	0	2	4	5
Zinc	ppm	ASTM D5185m	0	70	59	27
Sulfur	ppm	ASTM D5185m	23500	19060	17982	18032
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	0	<1
Sodium	ppm	ASTM D5185m		6	3	14
Potassium	ppm	ASTM D5185m	>20	<1	0	0
Water	%	ASTM D6304	>0.05	0.013	0.005	△ 0.223
ppm Water	ppm	ASTM D6304	>500	137.0	50.2	▲ 2230
FLUID CLEANLIN	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		2247	10039	1333
Particles >6µm		ASTM D7647	>1300	538	△ 3131	726
Particles >14µm		ASTM D7647	>80	60	<u>^</u> 267	<u> </u>
Particles >21µm		ASTM D7647	>20	19	<u>^</u> 62	4 1
Particles >38µm		ASTM D7647	>4	1	<u>^</u> 6	6
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	18/16/13	△ 19/15	△ 17/14
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
A	1/0111	4.0TM D00 :=	4.0	0.00	0.05	0.070

0.35

0.372



OIL ANALYSIS REPORT

