

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id KAESER BSD 50 6341460 (S/N 1869)

Compressor

KAESER SIGMA (OEM) S-460 (--- QTS)

Recommendation Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is a moderate amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

				احضه حضه د		
CAMPLE INCODA	AATIONI	Jun2019	Mar2020 Sep2020	Apr2021 0ct2021	Sep2022	histow.0
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCP50325	KCP36119	KCP32617
Sample Date		Client Info		02 Sep 2022	31 Oct 2021	06 Apr 2021
Machine Age	hrs	Client Info		18530	13323	10585
Oil Age	hrs	Client Info		5206	5097	2359
Oil Changed		Client Info		Changed	Changed	Not Changd
Sample Status				ATTENTION	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	<1	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	<1	0
Aluminum	ppm	ASTM D5185m	>10	<1	0	<1
Lead	ppm	ASTM D5185m	>10	0	<1	0
Copper	ppm	ASTM D5185m	>50	15	29	3
Tin	ppm	ASTM D5185m	>10	0	0	0
Antimony	ppm	ASTM D5185m			<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	10
Barium	ppm	ASTM D5185m	90	0	0	30
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	0
Magnesium	ppm	ASTM D5185m	90	13	26	63
Calcium	ppm	ASTM D5185m	2	0	0	2
Phosphorus	ppm	ASTM D5185m		2	4	4
Zinc	ppm	ASTM D5185m		16	21	
				10	Z I	11
Sulfur	ppm	ASTM D5185m		17515	18285	11 13282
Sulfur CONTAMINANTS		ASTM D5185m method	limit/base			13282
CONTAMINANTS			limit/base	17515	18285	13282
CONTAMINANTS	3	method		17515 current	18285 history1	13282 history2
CONTAMINANTS Silicon Sodium	ppm	method ASTM D5185m		17515 current	18285 history1 <1	13282 history2
CONTAMINANTS Silicon Sodium Potassium	ppm ppm	method ASTM D5185m ASTM D5185m	>25 >20	17515 current 0 5	18285 history1 <1 15	13282 history2 0 20
CONTAMINANTS Silicon Sodium Potassium Water	ppm ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m	>25 >20	17515 current 0 5	18285 history1 <1 15 7	13282 history2 0 20 4
CONTAMINANTS Silicon Sodium Potassium Water	ppm ppm ppm % ppm	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D6304	>25 >20 >0.05	17515 current 0 5 2 0.018	18285 history1 <1 15 7 0.018	13282 history2 0 20 4 0.021 213.8
CONTAMINANTS Silicon Sodium Potassium Water opm Water FLUID CLEANLIN	ppm ppm ppm % ppm	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304	>25 >20 >0.05 >500	17515 current 0 5 2 0.018 182.4	18285 history1 <1 15 7 0.018 183.2	13282 history2 0 20 4 0.021 213.8
CONTAMINANTS Silicon Sodium Potassium Water opm Water FLUID CLEANLIN Particles >4µm	ppm ppm ppm % ppm	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 method	>25 >20 >0.05 >500	17515 current 0 5 2 0.018 182.4 current	18285 history1 <1 15 7 0.018 183.2 history1	13282 history2 0 20 4 0.021 213.8 history2
CONTAMINANTS Silicon Sodium Potassium Water opm Water FLUID CLEANLIN Particles >4µm Particles >6µm	ppm ppm ppm %	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 method ASTM D7647	>25 >20 >0.05 >500 limit/base	17515 current 0 5 2 0.018 182.4 current 6076	18285 history1 <1 15 7 0.018 183.2 history1 3547	13282 history2 0 20 4 0.021 213.8 history2 2272
CONTAMINANTS Silicon Sodium Potassium Water opm Water FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm	ppm ppm ppm %	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 Method ASTM D7647 ASTM D7647	>25 >20 >0.05 >500 limit/base	17515 current 0 5 2 0.018 182.4 current 6076 2023	18285 history1 <1 15 7 0.018 183.2 history1 3547 954	13282 history2 0 20 4 0.021 213.8 history2 2272 814
CONTAMINANTS Silicon Sodium Potassium Water ppm Water FLUID CLEANLIN Particles >4µm Particles >14µm Particles >21µm	ppm ppm ppm %	method ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 ASTM D6304 method ASTM D7647 ASTM D7647 ASTM D7647	>25 >20 >0.05 >500 limit/base >1300 >80	17515 current 0 5 2 0.018 182.4 current 6076 2023 158	18285 history1 <1 15 7 0.018 183.2 history1 3547 954 70	13282 history2 0 20 4 0.021 213.8 history2 2272 814 95
Silicon Sodium Potassium Water ppm Water	ppm ppm ppm %	method ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 ASTM D6304 method ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>25 >20 >0.05 >500 limit/base >1300 >80 >20 >4	17515 current 0 5 2 0.018 182.4 current 6076 2023 158 29	18285 history1 <1 15 7 0.018 183.2 history1 3547 954 70 20	13282 history2 0 20 4 0.021 213.8 history2 2272 814 95 28
CONTAMINANTS Silicon Sodium Potassium Water opm Water FLUID CLEANLIN Particles >4µm Particles >14µm Particles >21µm Particles >38µm	ppm ppm ppm %	method ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 ASTM D6304 method ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>25 >20 >0.05 >500 limit/base >1300 >80 >20 >4	17515 current 0 5 2 0.018 182.4 current 6076 2023 158 29 4	18285 history1 <1 15 7 0.018 183.2 history1 3547 954 70 20 1	13282 history2 0 20 4 0.021 213.8 history2 2272 814 95 28 2



OIL ANALYSIS REPORT

